

LED floodlight without sensor

XLED ONE XL

Anthracite
EAN 4007841 065225
Article number 065225



LED

long life LED 50.000 h

3000 K

3000K warm-white



IP44



Panel 180° vertical



indoor/outdoor light



energy saving

3 years

manufacturer's warranty



Light source not exchangeable



Control gear not exchangeable



CE

Function description

Powerful lighting very big on style. The XLED ONE XL with an output of 42,6 W delivers a powerful 3000 K and of warm white light. Tilting through 180°, the wall and ceiling spot is fitted with high-quality and particularly long-lasting LEDs with a service life of a good 30 years – without any ifs or buts. Protection class: IP44.

Technical specifications

Dimensions (L x W x H)	193 x 259 x 215 mm
With lamp	Yes, STEINEL LED system
With motion detector	No
Manufacturer's Warranty	3 years
Version	Anthracite
PU1, EAN	4007841065225
Application, place	Outdoors
Application, room	outdoors, courtyard & driveway
Installation site	wall, ceiling
Installation	Wall, Ceiling, Surface wiring
Impact resistance	IK03
IP-rating	IP44
Protection class	I
Ambient temperature	-20 – 40 °C
Housing material	Aluminium

Cover material	Glass transparent
Mains power supply	220 – 240 V / 50 – 60 Hz
Photo-cell controller	No
Luminous flux total product	4200 lm
Total product efficiency	99 lm/W
Colour temperature	3000 K
Colour variation LED	SDCM3
Lamp	LED cannot be replaced
LED life expectancy (max. °C)	50000 h
Service life LED L70B50 (25°)	> 36000 h
Drop in luminous flux in accordance with LM80	L70B10
LED cooling system	Passive Thermo Control
Basic light level function	No
Output	42,6 W
Colour Rendering Index CRI	= 80

<https://www.steinell.de>

Subject to technical modifications

09.2023 Page 1 from 2

LED floodlight without sensor

XLED ONE XL


Anthracite

EAN 4007841 065225

Article number 065225



Dimension Drawing



Circuit diagram

