

BALI S LED1X4150 G259 T830 DPRZ LT80 • 1110957



Product:	Bali S LED1x4150 G259 T830 DPRZ LT80
Order code:	1110957
Family:	Bali S LED
Product group:	Surface and suspended luminaires

GENERAL DATA

Description:	Surface mounted LED luminaire Light distribution type: direct Optical system: matt micro-prismatic PMMA diffuser, low-glare/translucent micro-prismatic PMMA diffuser Housing: steel Colour: white RAL9003
Installation:	On the ceiling (mounting brackets included). Push-in terminal, 3x2x2.5mm2
Environment	Indoor
Application	office, education, retail, public place

ELECTRICAL DATA

Mains voltage:	220-240V, 0/50/60Hz	System power*, W:	31.8
Power factor:	>0,90	Control gear:	ECG on/off
Integrated sensor:	None	Connection:	Push-in terminal, 3x2x2.5mm2

LIGHTING DATA

Light source and cap, W:	LED	Light source included:	yes
Luminaire output*, lm(ta+25°C):	3922	System efficacy, lm/W:	123
CRI (Ra):	80+	CCT, K:	3000
SDCM:	3	Light Distribution:	Wide-wide beam (C0-C180 plane 76°...125°, C90-C270 plane 76°...125°)
Distribution Type:	Direct	Beam angle, °:	86x90
LED lifetime, h:	50000/L80B10	Ripple current (≤120 Hz), %:	≤3


TECHNICAL DATA

Net weight, kg:	3.55	Quantity in package, pcs:	1
Packaging volume, m3/pcs:	0.0067	Pallet quantity, pcs:	132
Dimensions, mm:	1416x56x81		


STANDARDS

Operating temperature range, °C:	ta 0...+35	Protection class IEC:	I
Ingress protection code:	IP40	Mechanical impact resistance:	IK05
EEC:	D	Certificates:	CE, RoHS
Warranty:	3 years (5 years - see warranty Ts and Cs)		

Technical drawing (.jpg)



Light distribution curve (.jpg)



Note:

Tolerance range for optical and electrical data: $\pm 10\%$. Values apply to an ambient temperature of 25 C. NORTHCLIFFE LIGHTING is constantly developing and improving its products. The right is reserved to change any product specifications without prior notification. Photos are for illustrational purposes only. The exact appearance of the product may vary depending on the monitor settings, options selected and other factors.