NORTHCLIFFE MAKING LIFE BRIGHTER

TAURUS 1PLED G08 DELUXE TEST • 1019238



Product:	Taurus 1PLED G08 Deluxe TEST	
Order code:	1019238	
Family:	Taurus LED	
Product group: Emergency lighting		


GENERAL DATA

Description:	Surface mounted double-sided LED emergency exit sign Light distribution type: omnidirectional	
	Optical system: clear PMMA diffuser	
	Housing: extruded aluminium	
	Colour: light grey	
	Battery charging time: 24 hours	
	Battery: NiCd, deep discharge protection	
	Recognition distance: 30 meters	
Instalation:	On the ceiling or wall (mounting brackets included), or suspended (requires an accessory). Push-in terminal, 4x2x2.5mm2	
Environment	Indoor	
Application	emergency exit sign	

ELECTRICAL DATA

220-240V, 50/60Hz	System power*, W:	1
>0,60	Control gear:	ECG on/off
M/NM	Emergency operating time, h:	1
Push-in terminal, 4x2x2.5mm2		
LED	Light source included:	yes
80+	ССТ, К:	6500
3	Light Distribution:	Other
Omnidirectional	LED lifetime, h:	50000/L80B50
1.2	Quantity in package, pcs:	1
0.003857868	Pallet quantity, pcs:	256
ta 0+40	Protection class IEC:	I
IP41	Mechanical impact	IK02
	racistanca	
CE, RoHS	Warranty:	2 years
	>0,60 M/NM Push-in terminal, 4x2x2.5mm2 LED 80+ 3 Omnidirectional 1.2 0.003857868 ta 0+40	>0,60Control gear:M/NMEmergency operating time, h:Push-in terminal, 4x2x2.5mm2LEDLight source included:80+CCT, K:3Light Distribution:OmnidirectionalLED lifetime, h:1.2Quantity in package, pcs:0.003857868Pallet quantity, pcs:ta 0+40Protection class IEC:

Technical drawing (.jpg)



Note:

*: M-maintained (with an option of connecting as non-maintained), NM- non-maintained, system power and output indicates data in emergency mode, tolerance range for optical and electrical data: $\pm 10\%$, values apply to an ambient temperature of 25°C

Date of issue: 2021-07-09 NORTHCLIFFE LIGHTING, UAB Raudondvario pl. 101, LT-47184 Kaunas, Lithuania info@northcliffe.org