

AXPK-PE 4G95

1kV underground cable with aluminum conductors



APPLICATION

Power cable with aluminium conductor. For fixed outdoor installation, perfect for ploughing down.

CERTIFICATIONS AND DESIGN STANDARDS



HD 603-5D
EN 60228
IEC 60502-1
HD 308 S2

Distribution cables of rated voltage 0,6/1 kV
Conductor standard
1 kV & 3 kV power cables with extruded insulation.
Identification of cores in cables and flexible cords

Conductor material	Aluminium
Conductor surface	Bare
Core insulation material	XLPE
Core identification (acc. HD 308 S2)	Yes
Material outer sheath	Polyethylene (PE)
Max. conductor temperature [°C]	90
Max. conductor temperature at short circuit [°C]	250
Permitted cable outer temperature during assembling/handling (min) [°C]	-20
Bending radius (rule)	12xD
Reaction-to-fire class (acc. EN 13501-6)	Fca

PRODUCT PROPERTIES

Conductor category	Class 2 = stranded
Shape of conductor	Sector-shaped
Nominal cross section conductor [mm²]	95
Number of cores	4
With protective conductor	Yes
Colour outer sheath	Black
Nominal outer diameter [mm]	34
Conductor resistance at 20° C [Ohm/km]	0.32
Current carrying capacity in air [A]	236
Current carrying capacity in ground [A]	220
Cable weight [kg/km]	1,360
Min. bending radius during installation [mm]	400
DOP number	1016413

Current load in air, installation method E, temperature 25°C
Current load in ground, installation method D2 (directly in ground). Ground temperature 15°C, thermal resistivity 1,0 K·m/W

Item name	EAN-code (GTIN)	Packaging type	Standard packaging quantity
AXPK-PE 4G95 0,6/1 kV	4741532130358	Drum	500