

PRODUCT-DETAILS

UK620MVB

UK620MVB Multimedia unit , 497 mm x 384 mm x 97 mm, Flush mounting, IP30, Single



General Information

Extended Product Type	UK620MVB
Product ID	2CPX031454R9999
EAN	4011617314547
Catalog Description	UK620MVB Multimedia unit , 497 mm x 384 mm x 97 mm, Flush mounting, IP30, Single
Long Description	Multimedia unit, series UK600, Expansion option: Lateral and bottom, for the internal use, with closed doorframe and door, class of protection II (double insulated), degree of protection IP30, applicable standards: EN 60670-24, IK code 7, Rated operational voltage 400V AC 50/60 Hz, rated current 63 A, Glow wire resistance 850°C, Powder-coated, in RAL 9016, enclosure out of thermoplast, with frame and ventilated door , door out of sheet steel, in RAL 9016, with TIP-in closure, door opening angle 120 degree, door hinge right or left, cable entry on top via cable entry slide part is pre-punched, on bottom via cable entry slide part is pre-punched, on side via pre-punched, rear wall pre-punched, dimensions in mm (H x W x D): 497 x 384 x 97, Shutter frame dimensions in mm (H x W x D): 497 x 384 x 9, cable fastening rail integrated, assembled with perforated sheet steel mounting plate and DIN rail

Technical

Standards	DIN 43871
Rated Operational Voltage	Maximum 400 V
Operational Voltage	400 V
Rated Current (I _n)	63 A
Power Loss	Δt = 30K 100 W

Number of Miniature Circuit Breakers (MCBs)	"
Number of Rows	2
Closure Type	Push Button
Configuration Type	assembled with perforated sheet steel mounting plate and DIN rail
Cover Plate Type	Door
Enclosure Type	Multimedia unit
Mounting Type	Flush mounting
Door Type	Single
Surface Finishing	Powder-coated
Housing Material	Plastic
Cover Style	Closed
RAL Number	RAL 9016 - Traffic White
Color	Traffic white
Terminal Type	No Terminals

Material Compliance

RoHS Information	2CPC100018X0201
RoHS Status	Following EU Directive 2011/65/EU and Amendment 2015/863 July 22, 2019
RoHS Date	20230918
REACH Declaration	2CPC100005X0201
REACH Information	False - does not contains substances > 0.1 mass percentage
Conflict Minerals Reporting Template (CMRT)	9AKK108468A3363

Environmental

Degree of Protection	IP30
Protection Class	Isolated (Class II)

Dimensions

Width in Number of Modular Spacings	12
Product Net Width	384 mm
Product Net Height	497 mm
Product Net Depth / Length	97 mm
Product Net Weight	2.936 kg
Built-In Depth (t ₂)	81 mm
Dimension Diagram	2CPC000001D0201 2CPC000003D0201 2CPC000004D0201 2CPC000007D0201

Ordering

Package Level 1 Units	pack 1 piece
Package Level 1 Gross Weight	3.053 kg

Certificates and Declarations

Declaration of Conformity - CE	2CPC100018X0201
-----------------------------------	-----------------

Installation

Instructions and Manuals	2CPC130102M5601
--------------------------	-----------------

Popular Downloads

Data Sheet, Technical Information	No document needed
-----------------------------------	--------------------

Classifications

ETIM 8	EC000214 - Small distribution board
ETIM 9	EC000214 - Small distribution board
WEEE Category	4. Large Equipment (Any External Dimension More Than 50 cm)
WEEE B2C / B2B	Business To Consumer
CN8	85381000
eClass	V11.0 : 27142409
Object Classification Code	U

Categories

Low Voltage Products and Systems → Enclosures → Consumer Units → Consumer Units → UK600

