

Industrial luminarie Inda Bas LED, 22-30W, IP65, 4000K, 160lm

Item: 7298128

MALMBERGS



Product information

Robust, energy-efficient and easy-to-install industrial luminaire with high IP rating, ideal for really tough environments. Connection spaces in both ends and pre-installed through-wiring. D-marked. Adjustable wattage in two increments with DIP switch. Suitable for use in most industrial areas, parking garages, warehouses etc.

Mounting

Key hole for surface mounting in ceiling. Integrated wire bracket with lockable hook for suspension on wire. Can also be mounted on rail.

Connection

Fast connection terminal block 3x1.5 mm², one on each end. Incl. through-wiring 3G1.5 mm². Cable inlet, Ø 20 mm, one on each end, with cable gland and rubber sealing in both ends.

Description

Grey body made of polycarbonate, opal diffuser made of polycarbonate. Incl. LED module and driver.

No. of drivers per MCB

B10 – 17 pc

B16 – 27 pc

C10 – 24 pc

C16 – 39 pc

Industrial luminarie Inda Bas LED, 22-30W, IP65, 4000K, 160

Item: 7298128

MALMBERGS

Specifications

Beam angle	110°
Brand	Malmbergs Pro
Colour	Grey
Colour consistency	3 SDCM
Colour rendering index (CRI)	Ra80
Colour temperature	4000K
Description	With sensor (optional)
Dimmable	No
Dims (LxWxH)	1200x61x57 mm
Efficiency	160lm/W
Impact protection	IK08
IP rating	IP65
Lifetime	100 000 hrs (L80 B10)
Luminous flux	3520-4800lm
Power	22-30W
Weight	0.7 kg
Voltage	230V