

# Product datasheet

Specifications



Modular enclosure, PrismaSeT XS, surface, 1 x 13 modules, 1 earth + 1 neutral terminal blocks, plain white door

LVSXQ113

## Main

Range	PrismaSeT
Product Name	XS
Product Or Component Type	Enclosure
Enclosure Type	Distribution enclosure
Enclosure Mounting	Surface

## Complementary

Width	336 mm total:
Height	300 mm total:
Depth	151 mm total:
Internal Depth	135 mm
Number Of 18 Mm Modules Per Row	13
Number Of Horizontal Rows	1
Total Number Of 18 Mm Modules	13
9 Mm Pitches	26
Electrical Insulation Class	Class II
Provided Equipment	1 identification label 1 label protector 2 terminal block 1 blanking plate strip 1 door 1 DIN rail 1 back plate
Type Of Front Plate	Modular
Door Type	Plain
Type Of Rail	Symmetrical DIN
Mounting Plate Description	Without mounting plate
Power Dissipation In W	22 W
[In] Rated Current	63 A
[Ui] Rated Insulation Voltage	400 V
Cable Entry	Cable or tube Cut-out plates Trunking Removable plates
Number Of Terminal Blocks	1 earth with 8 outgoing 1 neutral with 8 outgoing

<b>Distribution Block Outgoers</b>	4 x 16 mm <sup>2</sup> + 4 x 10 mm <sup>2</sup> for earth 4 x 16 mm <sup>2</sup> + 4 x 10 mm <sup>2</sup> for neutral
<b>Connections - Terminals</b>	Screw connection (earth) , 4 x 16 mm <sup>2</sup> Screw connection (earth) , 4 x 10 mm <sup>2</sup> Screw connection (neutral) , 4 x 16 mm <sup>2</sup> Screw connection (neutral) , 4 x 10 mm <sup>2</sup>
<b>Locking Options Description</b>	Keylock option
<b>Enclosure Material</b>	Back part: technoplastic Enclosure: technoplastic Front plate: technoplastic Door: technoplastic
<b>Net Weight</b>	2.200 kg
<b>Colour</b>	Enclosure: white (RAL 9003) Front plate: white (RAL 9003) Door: white (RAL 9003)
<b>Market Segment</b>	Residential Small buildings

## Environment

<b>Fire Resistance</b>	Back plate: 650 °C conforming to IEC 60695-2-11 Enclosure: 650 °C conforming to IEC 60695-2-11 Front plate: 650 °C conforming to IEC 60695-2-11 Door: 650 °C conforming to IEC 60695-2-11
<b>Ip Degree Of Protection</b>	IP40 with closed door
<b>Ik Degree Of Protection</b>	IK09 with closed door
<b>Overvoltage Category</b>	II
<b>Ambient Air Temperature For Operation</b>	-25...60 °C
<b>Standards</b>	IEC 60670-1 IEC 60670-24 IEC 61439-1 IEC 61439-3
<b>Quality Labels</b>	IMQ

## Packing Units

<b>Unit Type Of Package 1</b>	PCE
<b>Number Of Units In Package 1</b>	1
<b>Package 1 Height</b>	15.700 cm
<b>Package 1 Width</b>	32.000 cm
<b>Package 1 Length</b>	34.800 cm
<b>Package 1 Weight</b>	2.220 kg
<b>Unit Type Of Package 2</b>	P12
<b>Number Of Units In Package 2</b>	40
<b>Package 2 Height</b>	91.000 cm
<b>Package 2 Width</b>	80.000 cm
<b>Package 2 Length</b>	120.000 cm
<b>Package 2 Weight</b>	98.000 kg

## Sustainability

**Green Premium™ label** is Schneider Electric's commitment to delivering products with best-in-class environmental performance. Green Premium promises compliance with the latest regulations, transparency on environmental impacts, as well as circular and low-CO<sub>2</sub> products.

**Guide to assessing product sustainability** is a white paper that clarifies global eco-label standards and how to interpret environmental declarations.

[Learn more about Green Premium >](#)

[Guide to assess a product's sustainability >](#)



Transparency RoHS/REACH

## Well-being performance

✓ Reach Free Of Svhc

✓ Toxic Heavy Metal Free

✓ Mercury Free

✓ Rohs Exemption Information Yes

✓ Halogen Free Product

## Certifications & Standards

**Reach Regulation**

[REACH Declaration](#)

**Eu Rohs Directive**

Pro-active compliance (Product out of EU RoHS legal scope)

[EU RoHS Declaration](#)

**China Rohs Regulation**

[China RoHS declaration](#)

Pro-active China RoHS declaration (out of China RoHS legal scope)

**Environmental Disclosure**

[Product Environmental Profile](#)

**Circularity Profile**

No need of specific recycling operations