# Eaton 3S850D

## Catalog Number: 3S850D

Eaton 3S Gen2 UPS DIN, 850 VA, 510 W, Input: Schuko, Outputs: (4) Schuko, (4) Schuko surge only, USB Communication, USB charge (2), Tower

## Photo is representative

# **General Specifications**

**Product Name** 

Eaton 3S Gen2 UPS

3S850D

Product Length/Depth

**Product Height** 

Catalog Number

83.5 mm

170 mm

**Product Width** 

Product Weight

335 mm

4.2 kg

Compliances

Certifications EAC

CE Marked

IEC/EN 62040-2

CE

IEC/EN 62040-1



#### UPC

743172101778

## **Battery**

Battery type

Sealed, lead-acid

Runtime graph

View runtime graph

Battery replacement

User replaceable

Battery quantity

1

Battery management

Replaceable batteries, Automatic battery test, deep-discharge protection, cold-start capable

Battery rating

12 V / 9 Ah

Extended battery capability

No

## Electrical output

Receptacle

(4) Schuko, (4) Schuko surge only

Voltage

230V

Wattage

510W

Output power factor

0.6

Output voltage range

184-264 V (adjustable to 161-284 V)

Output nominal voltage

230V default (220/230/240V)

Voltage distortion output (linear load) - max

0

Feed type

1

Topology

Offline

VA rating

850 VA

## Electrical input

Input connection

Protective contact (SCHUKO)

Input nominal voltage

230V default (220/230/240V)

Nominal frequency

50/60 Hz

Input cord length

1.5 m

Input voltage range

184-264 V (adjustable to 161-284 V)

Input frequency range

46-70 Hz

## Communications

Includes network card

No

Communication

USB port (HID compliant)

Ethernet interface

No

User interface

LEDs

Potential free switch contact

No

**Expansion slots** 

No

## Software compatibility

Eaton UPS Companion (enables safe system shutdown, energy usage metering and configuration of UPS settings)

## Type of interface

USB

## **Environmental**

Altitude

2000 m

Noise level

<25 dB at 1 meter

Relative humidity

0-85% non-condensing

## Additional specifications

## Construction type

Free standing model

## Package contents

USB cable

Quickstart guide

Safety instructions

#### Phase (output)

1

#### Auto shutdown function

Yes

Color

Black/White

## Efficiency

98

## Rack mounting kit

No

#### Phase (input)

1

## Surge protection

Yes

## Resources

#### **Brochures**

Eaton UPS and battery services - EN

Eaton UPS Services Quick Guide - EN

Compliance information

CE-Eaton-3S-Gen2-UPS

Technical data sheets

Eaton 3S Gen2 UPS - Datasheet



Eaton Corporation plc Eaton House 30 Pembroke Road Dublin 4, Ireland Eaton.com

© 2024 Eaton. All rights reserved.

Eaton is a registered trademark.

All other trademarks are property of their respective owners.



Eaton.com/socialmedia