

# Product datasheet

Specifications



## CONNECTOR 32A 5 MODULES

Local distributor code:

2222352

KSB32CM55

EAN Code: 3606480005978

### Main

Range Of Product	Canalis
Range Compatibility	Canalis KS busbar trunking
Product Or Component Type	Tap-off unit
Busbar Trunking Compatibility	Canalis KS busbar trunkingplug-in
[Ie] Rated Operational Current	32 A
Protection Type	Circuit breaker: miniature circuit breaker (MCB)
Mounting Mode	Plug-in with fixed polarity
Tap-Off Unit Polarity	3L+N+PE
Colour	White (RAL 9001)

### Complementary

Device Application	Medium power distribution
Provided Equipment	circuit-breaker to be ordered separately blanking plate
[Ue] Rated Operational Voltage	230...690 V depending on protective device
[Uiimp] Rated Impulse Withstand Voltage	6.8 kV
[Ui] Rated Insulation Voltage	400 V depending on protective device 500 V depending on protective device 690 V depending on protective device
Network Frequency	50/60 Hz
Electrical Connection	Pre-wired terminal block - ISO32 6 mm <sup>2</sup> flexible Pre-wired terminal block - ISO32 10 mm <sup>2</sup> rigid
Door/Cover Opening Side	Front
Tap-Off Unit Disconnection Mode	By drawing out
Standards	IEC 61439-6 IEC 61439-1
Body Material	Plastic
18 Mm Pitches	5
Width	135 mm
Depth	108 mm
Height	175 mm
Net Weight	0.6 kg

### Environment

---

<b>Earthing System</b>	TT TN-S IT
<b>Ip Degree Of Protection</b>	IP55 conforming to IEC 60529
<b>Ik Degree Of Protection</b>	IK08 conforming to IEC 62262

---

## Packing Units

---

<b>Unit Type Of Package 1</b>	PCE
<b>Number Of Units In Package 1</b>	1
<b>Package 1 Height</b>	16.500 cm
<b>Package 1 Width</b>	15.500 cm
<b>Package 1 Length</b>	18.500 cm
<b>Package 1 Weight</b>	723.000 g
<b>Unit Type Of Package 2</b>	P12
<b>Number Of Units In Package 2</b>	119
<b>Package 2 Height</b>	80.000 cm
<b>Package 2 Width</b>	80.000 cm
<b>Package 2 Length</b>	120.000 cm
<b>Package 2 Weight</b>	103.000 kg

---

## Contractual warranty

---

<b>Warranty</b>	18 months
-----------------	-----------

## Sustainability

**Green Premium™ label** is Schneider Electric's commitment to delivering products with best-in-class environmental performance. Green Premium promises compliance with the latest regulations, transparency on environmental impacts, as well as circular and low-CO<sub>2</sub> products.

**Guide to assessing product sustainability** is a white paper that clarifies global eco-label standards and how to interpret environmental declarations.

[Learn more about Green Premium >](#)

[Guide to assess a product's sustainability >](#)



Transparency RoHS/REACH

## Well-being performance

 Reach Free Of Svhc

 Toxic Heavy Metal Free

 Mercury Free

 RoHS Exemption Information Yes

 Halogen Free Plastic Parts Product

## Certifications & Standards

**Reach Regulation**

[REACH Declaration](#)

**Eu RoHS Directive**

Compliant

[EU RoHS Declaration](#)

**China RoHS Regulation**

[China RoHS declaration](#)

Pro-active China RoHS declaration (out of China RoHS legal scope)

**Environmental Disclosure**

[Product Environmental Profile](#)

**WEEE**

The product must be disposed on European Union markets following specific waste collection and never end up in rubbish bins

**Circularity Profile**

No need of specific recycling operations