

ZCMD25L2

Limit switch body, Limit switches XC Standard, ZCMD, 1NC+1 NO, silver, slow break, connection, 2 m



Galvenā

Produkta sērija	Telemecanique Limit switches XC Standard
Series name	Standard format
Produkta vai sastāvdaļas veids	Limit switch body
Ieīces īsais nosaukums	ZCMD
Design	Miniature
Body type	Fixed
Associated head	ZCE65 ZCE27 ZCE62 ZCE64 ZCE28 ZCEG1 ZCE11 ZCE67 ZCE01 ZCE10 ZCEF2 ZCE09 ZCE21 ZCE24 ZCE08 ZCE07 ZCE66 ZCE63 ZCE29 ZCEF0 ZCE13 ZCE02 ZCE14 ZCE06
Body material	Zamak
Polu skaits	2
Kontaktlīgšanas tips	1 NC + 1 NO
Contact operation	Slow-break Slow-break, break before make

Papildinošs

Produktu saderība	XCMD
Electrical connection	Removable cable
Kabeļa garums	2 m
Cable composition	5 x 0.75 mm ²
Wire insulation material	PvR
Contacts insulation form	Zb
Kontaktlīgšanas materiāls	Sudraboti kontakti
Positive opening	With
Minimum actuation speed	6 m/min
[Ui] rated insulation voltage	300 V 3)UL 508 400 V 3)IEC 60947-5-1 300 V 3)CSA C22.2 No 14
Maximum resistance across terminals	25 mhm IEC 60255-7 category 3
[Uimp] rated impulse withstand voltage	4 KV IEC 60664 4 KV IEC 60947-1

The information provided in this documentation contains general descriptions and/or technical characteristics of the performance of the products contained herein. This documentation is not intended as a substitute for and is not to be used for determining suitability or reliability of these products for specific user applications. It is the duty of any such user or integrator to perform the appropriate and complete risk analysis, evaluation and testing of the products with respect to the relevant specific application or use thereof. Neither Schneider Electric Industries SAS nor any of its affiliates or subsidiaries shall be responsible or liable for misuse of the information contained herein.

Short-circuit protection	6 A cartridge fuse gG
Electrical durability	5000000 Cikli, DC-13 120 V, 3 W 60 cikls/mn 0,5 IEC 60947-5-1 appendix C 5000000 Cikli, DC-13 24 V, 4 W 60 cikls/mn 0,5 IEC 60947-5-1 appendix C 5000000 cikli, DC-13 48 V, 3 W 60 cikls/mn 0,5 IEC 60947-5-1 appendix C
Platums	30 mm
Augstums	50 mm
Dziļums	16 mm
Neto svars	0,065 kg




Vide

Apkārtējā gaisa temperatūra uzglabāšanai	-40...70 °C
--	-------------

Iepakojšanas vienības

Pirmā iepakojuma vienības tips	PCE
Vienību skaits 1. iepakojumā	1
1. iepakojuma augstums	3,0 cm
1. iepakojuma platums	15,0 cm
1. iepakojuma garums	15,0 cm
1. iepakojuma svars	238,0 g
Otrā iepakojuma vienības tips	PAL
Vienību skaits 2. iepakojumā	320
2. iepakojuma augstums	60,0 cm
2. iepakojuma platums	80,0 cm
2. iepakojuma garums	320,0 cm
2. iepakojuma svars	77,44 kg
Trešā iepakojuma vienības tips	S03
Vienību skaits 3. iepakojumā	40
3. iepakojuma augstums	30,0 cm
3. iepakojuma platums	30,0 cm
3. iepakojuma garums	40,0 cm
3. iepakojuma svars	10,137 kg

Piedāvājiēt ilgspēju

Ilgspējīgs piedāvājuma statuss	Green Premium izstrādājums
REACH regula	 REACH Deklarācija
ES RoHS direktīva	Proaktīva atbilstība (uz izstrādājumu neattiecas ES RoHS juridiskās saistības)  ES RoHS deklarācija
Nesatur dzīvsudrabu	Jā
Informācija par RoHS izņēmumiem	 Jā

Līguma garantija

Garantija	18 months
-----------	-----------