



Galvenā

Diapazons	ComPact
Produkta vai sastāvdaļas veids	Switch disconnecter
Produkta nosaukums	ComPacT INS
Polu skaits	4P
Tīkla veids	AC DC
Tīkla frekvence	50/60 Hz
[Ie] rated operational current	AC-22A 250 A AC 50/60 Hz 220/240 V AC-22A 250 A AC 50/60 Hz 380/415 V AC-22A 250 A AC 50/60 Hz 440/480 V AC-22A 250 A AC 50/60 Hz 480 V NEMA AC-22A 250 A AC 50/60 Hz 500/525 V AC-22A 250 A AC 50/60 Hz 660/690 V AC-23A 250 A AC 50/60 Hz 220/240 V AC-23A 250 A AC 50/60 Hz 380/415 V AC-23A 250 A AC 50/60 Hz 440/480 V AC-23A 250 A AC 50/60 Hz 480 V NEMA AC-23A 250 A AC 50/60 Hz 500/525 V AC-23A 250 A AC 50/60 Hz 660/690 V DC-22A 250 A DC 125 V 2 poles in series DC-22A 250 A DC 250 V 4 poles in series DC-23A 250 A DC 125 V 2 poles in series DC-23A 250 A DC 250 V 4 poles in series
[Ui] rated insulation voltage	750 V AC 50/60 Hz
[Ith] conventional free air thermal current	250 A 60 °C
[Icm] rated short-circuit making capacity	30 kA switch-disconnector alone 690 V AC 50/60 Hz 330 kA with upstream protection circuit breaker 690 V AC 50/60 Hz
[Ue] rated operational voltage	250 V DC 690 V AC 50/60 Hz
Suitability for isolation	Yes
Contact position indicator	Yes
Visible break	No
Pollution degree	3

Papildinošs

Vadības veids	Direct front rotary handle
Handle colour	Black
Montāžas veids	Fixed
Montāžas stiprinājums	Rail Plāksne
Upside connection	Front
Downside connection	Front

The information provided in this documentation contains general descriptions and/or technical characteristics of the performance of the products contained herein. This documentation is not intended as a substitute for and is not to be used for determining suitability or reliability of these products for specific user applications. It is the duty of any such user or integrator to perform the appropriate and complete risk analysis, evaluation and testing of the products with respect to the relevant specific application or use thereof. Neither Schneider Electric Industries SAS nor any of its affiliates or subsidiaries shall be responsible or liable for misuse of the information contained herein.

Maximum power	AC-23 132 kW 380/415 V AC 50/60 Hz AC-23 150 kW 440 V AC 50/60 Hz AC-23 150 kW 480 V AC 50/60 Hz (NEMA) AC-23 160 kW 500/525 V AC 50/60 Hz AC-23 210 kW 660/690 V AC 50/60 Hz AC-23 75 kW 220/240 V AC 50/60 Hz AC-23 75 kW 230 V AC 50/60 Hz (NEMA)
Rated duty	Uninterrupted
[I _{cw}] rated short-time withstand current	1,8 kA 30 s IEC 60947-3 2,2 kA 20 s IEC 60947-3 4,9 kA 3 s IEC 60947-3 8,5 kA 1 s IEC 60947-3
Mechanical durability	15000 cikli
Electrical durability	AC-22A 1500 cikli 440 V AC 50/60 Hz AC-22A 1500 cikli 500 V AC 50/60 Hz AC-22A 1500 cikli 690 V AC 50/60 Hz AC-23A 1500 cikli 440 V AC 50/60 Hz AC-23A 1500 cikli 500 V AC 50/60 Hz AC-23A 1500 cikli 690 V AC 50/60 Hz DC-22A 1500 cikli 250 V DC 4 poles in series DC-23A 1500 cikli 250 V DC 4 poles in series
Connection pitch	35 mm
Augstums	136 mm
Platums	140 mm
Dziļums	96 mm
Neto svars	2,2 kg

Vide

Standarti	IEC 60947-3 IEC 60947-1
Produkta sertifikācija	KEMA-KEUR[RETURN]CCC
IP aizsardzības pakāpe	IP40 atbilst IEC 60529
Triecienizturības klase (IK)	IK07 conforming to EN 50102
Apkārtējā gaisa temperatūra darbībai	-25...70 °C
Apkārtējā gaisa temperatūra uzglabāšanai	-50...85 °C

Iepakojšanas vienības

Pirmā iepakojuma vienības tips	PCE
Vienību skaits 1. iepakojumā	1
1. iepakojuma augstums	17,000 cm
1. iepakojuma platums	13,700 cm
1. iepakojuma garums	16,300 cm
1. iepakojuma svars	2,420 kg
Otrā iepakojuma vienības tips	S04
Vienību skaits 2. iepakojumā	9
2. iepakojuma augstums	30,000 cm
2. iepakojuma platums	40,000 cm
2. iepakojuma garums	60,000 cm
2. iepakojuma svars	22,654 kg
Trešā iepakojuma vienības tips	P12
Vienību skaits 3. iepakojumā	36
3. iepakojuma augstums	50,000 cm
3. iepakojuma platums	80,000 cm
3. iepakojuma garums	120,000 cm
3. iepakojuma svars	102,616 kg

Piedāvājiel ilgtspēju

Ilgtspējigs piedāvājuma statuss	Green Premium izstrādājums
REACH regula	REACH Deklarācija
ES RoHS direktīva	Atbilst izņēmumiem
Nesatur dzīvsudrabu	Jā
Ķīnas RoHS regula	Ķīnas RoHS Deklarācija
Informācija par RoHS izņēmumiem	Jā
Vides informācijas publicēšana	Produkta Ietekme Uz Vidi
Cirkularitātes profils	Informācija Par Eksploatācijas Izbeigšanu
WEEE	Eiropas Savienības tirgū no šī produkta ir jāatbrīvojas, ievērojot noteiktu atkritumu savākšanas kārtību, un produkts nedrīkst nonākt sadzīves atkritumu tvertnēs.

Līguma garantija

Garantija	18 months
-----------	-----------