



### Galvenā

Diapazons	ComPact
Produkta nosaukums	ComPact INS
Produkta vai sastāvdaļas veids	Switch disconnecter
Polu skaits	3P
Tīkla veids	AC DC
Tīkla frekvence	50/60 Hz
[Ie] rated operational current	AC-22A 100 A AC 50/60 Hz 220/240 V AC-22A 100 A AC 50/60 Hz 380/415 V AC-22A 100 A AC 50/60 Hz 440/480 V 2 poles in series AC-22A 100 A AC 50/60 Hz 500 V 2 poles in series AC-22A 100 A AC 50/60 Hz 660/690 V AC-23A 100 A AC 50/60 Hz 220/240 V AC-23A 100 A AC 50/60 Hz 380/415 V AC-23A 100 A AC 50/60 Hz 440/480 V AC-23A 100 A AC 50/60 Hz 500 V AC-23A 63 A AC 50/60 Hz 660/690 V DC-22A 100 A DC 50/60 Hz 125&nbsp;V 2 poles in series DC-23A 100 A DC 50/60 Hz 125&nbsp;V 2 poles in series
[Ui] rated insulation voltage	750 V AC 50/60 Hz
[Uimp] rated impulse withstand voltage	8 kV
[Ith] conventional free air thermal current	100 A 60 °C
[Icm] rated short-circuit making capacity	154 kA with upstream protection circuit breaker 690 V AC 50/60 Hz 20 kA switch-disconnector alone 690 V AC 50/60 Hz
[Ue] rated operational voltage	125&nbsp;V DC 690 V AC 50/60 Hz
Suitability for isolation	Yes
Contact position indicator	Yes
Visible break	No
Pollution degree	3

### Papildinošs

Vadības veids	Rotary handle
Handle colour	Black
Montāžas veids	Fixed
Montāžas stiprinājums	Plāksne DIN sliede
Upside connection	Front
Downside connection	Front
Maximum power	AC-23 22 kW 220/240 V AC 50/60 Hz AC-23 45 kW 380/415 V AC 50/60 Hz AC-23 55 kW 440 V AC 50/60 Hz AC-23 55 kW 500/525 V AC 50/60 Hz AC-23 55 kW 660/690 V AC 50/60 Hz

The information provided in this documentation contains general descriptions and/or technical characteristics of the performance of the products contained herein. This documentation is not intended as a substitute for and is not to be used for determining suitability or reliability of these products for specific user applications. It is the duty of any such user or integrator to perform the appropriate and complete risk analysis, evaluation and testing of the products with respect to the relevant specific application or use thereof. Neither Schneider Electric Industries SAS nor any of its affiliates or subsidiaries shall be responsible or liable for misuse of the information contained herein.

Rated duty	Uninterrupted
Intermittent duty class	Class 120 - 60 %
Enclosure dimensions for lthe	260 mm x 160 mm x 55 mm
[Icw] rated short-time withstand current	0,01 KA 30 s IEC 60947-3 1,23 KA 20 s IEC 60947-3 3,175 KA 3 s IEC 60947-3 5,5 kA 1 s IEC 60947-3
Mechanical durability	15000 cikli
Electrical durability	AC-22A 1500 cikli 220/240 V AC 50/60 Hz AC-22A 1500 cikli 380/415 V AC 50/60 Hz 2 poles in series AC-22A 1500 cikli 440 V AC 50/60 Hz AC-22A 1500 cikli 500 V AC 50/60 Hz AC-23A 1500 cikli 220/240 V AC 50/60 Hz AC-23A 1500 cikli 380/415 V AC 50/60 Hz AC-23A 1500 cikli 440 V AC 50/60 Hz AC-23A 1500 cikli 500 V AC 50/60 Hz DC-22A 1500 cikli 250 V DC 50/60 Hz 2 poles in series DC-23A 1500 cikli 250 V DC 50/60 Hz 2 poles in series AC-22A 1500 cikli 690 V AC 50/60 Hz AC-23A 1500 cikli 690 V AC 50/60 Hz 2 poles in series
Connection pitch	30 mm
Augstums	100 mm
Platums	135 mm
Dziļums	62,5 mm
Neto svars	0,8 kg

## Vide

Standarti	IEC 60947-3 IEC 60947-1
Produkta sertifikācija	CCC[RETURN]KEMA-KEUR
IP aizsardzības pakāpe	IP40 atbilst IEC&nbsp;60529
Triecienizturības klase (IK)	IK07 conforming to EN 50102
Apkārtējā gaisa temperatūra darbībai	-25...70 °C
Apkārtējā gaisa temperatūra uzglabāšanai	-50...85 °C

## Iepakojšanas vienības

Pirmā iepakojuma vienības tips	PCE
Vienību skaits 1. iepakojumā	1
1. iepakojuma augstums	13,400 cm
1. iepakojuma platums	11,500 cm
1. iepakojuma garums	15,400 cm
1. iepakojuma svars	1,024 kg
Otrā iepakojuma vienības tips	S03
Vienību skaits 2. iepakojumā	10
2. iepakojuma augstums	30,000 cm
2. iepakojuma platums	30,000 cm
2. iepakojuma garums	40,000 cm
2. iepakojuma svars	10,572 kg
Trešā iepakojuma vienības tips	P12
Vienību skaits 3. iepakojumā	80
3. iepakojuma augstums	44,000 cm
3. iepakojuma platums	80,000 cm
3. iepakojuma garums	120,000 cm
3. iepakojuma svars	99,000 kg

## Piedāvājiēt ilgtspēju

Ilgtspējīgs piedāvājuma statuss	Green Premium izstrādājums
REACH regula	<a href="#">REACH Deklarācija</a>
Nesatur REACH SVHC	Jā
ES RoHS direktīva	Atbilstīgs <a href="#">ES RoHS Deklarācija</a>
Nesatur toksiskus smagos metālus	Jā
Nesatur dzīvsudrabu	Jā
Ķīnas RoHS regula	<a href="#">Ķīnas RoHS Deklarācija</a>
Informācija par RoHS izņēmumiem	<a href="#">Jā</a>
Vides informācijas publicēšana	<a href="#">Produkta Ietekme Uz Vidi</a>
Cirkularitātes profils	<a href="#">Informācija Par Eksploatācijas Izbeigšanu</a>
WEEE	Eiropas Savienības tirgū no šī produkta ir jāatbrīvojas, ievērojot noteiktu atkritumu savākšanas kārtību, un produkts nedrīkst nonākt sadzīves atkritumu tvertnēs.

## Līguma garantija

Garantija	18 months
-----------	-----------