



Galvenā

Produkta sērija	INS250
Diapazons	TransferPacT ComPact
Ierīces īsais nosaukums	INS250
Produkta vai sastāvdaļas veids	Manual transfer switch
Ierīces pielietojums	Change source of supply
Saderība ar	ComPact (ComPacT INS) INS250 switch disconnector
Polu skaits	3P
Tīkla veids	AC DC
Tīkla frekvence	50/60 Hz
Montāžas veids	Fixed
Upside connection	Front
Downside connection	Front
Suitability for isolation	Yes
Contact position indicator	Yes
[Icm] rated short-circuit making capacity	30 kA switch-disconnector alone 690 V AC 50/60 Hz 330 kA with upstream protection circuit breaker 690 V AC 50/60 Hz

Papildinošs

Transfer switch class	PC
Number of contact position	3
Vadības veids	Direct front rotary handle
Darbības režīms	Manual
Montāžas stiprinājums	Rail Plāksne
Saslēgšanas veidu apraksts	Padlocking in OFF position
[Ie] rated operational current	AC-22A 250 A AC 50/60 Hz 220/240 V AC-22A 250 A AC 50/60 Hz 380/415 V AC-22A 250 A AC 50/60 Hz 440/480 V AC-22A 250 A AC 50/60 Hz 500/525 V AC-22A 250 A AC 50/60 Hz 660/690 V AC-23A 250 A AC 50/60 Hz 220/240 V AC-23A 250 A AC 50/60 Hz 380/415 V AC-23A 250 A AC 50/60 Hz 440/480 V AC-23A 250 A AC 50/60 Hz 500/525 V AC-23A 250 A AC 50/60 Hz 660/690 V DC-22A 250 A DC 125 V 2 poles in series DC-23A 250 A DC 125 V 2 poles in series
[Ith] conventional free air thermal current	250 A 60 °C
Rated duty	Uninterrupted
Intermittent duty class	Class 120 - 60 %
[Ui] rated insulation voltage	750 V AC 50/60 Hz
[Uimp] rated impulse withstand voltage	8 kV
[Ue] rated operational voltage	690 V AC 50/60 Hz IEC 60947-3 125 V DC IEC 60947-3

The information provided in this documentation contains general descriptions and/or technical characteristics of the performance of the products contained herein. This documentation is not intended as a substitute for and is not to be used for determining suitability or reliability of these products for specific user applications. It is the duty of any such user or integrator to perform the appropriate and complete risk analysis, evaluation and testing of the products with respect to the relevant specific application or use thereof. Neither Schneider Electric Industries SAS nor any of its affiliates or subsidiaries shall be responsible or liable for misuse of the information contained herein.

Mehāniskā bloķēšana	With mechanical interlocking
Mechanical durability	15000 cikli
Electrical durability	AC-22A 1500 cikli 440 V AC 50/60 Hz AC-22A 1500 cikli 500 V AC 50/60 Hz AC-22A 1500 cikli 690 V AC 50/60 Hz AC-23A 1500 cikli 440 V AC 50/60 Hz AC-23A 1500 cikli 500 V AC 50/60 Hz AC-23A 1500 cikli 690 V AC 50/60 Hz DC-22A 1500 cikli 125 V DC 2 poles in series DC-23A 1500 cikli 125 V DC 2 poles in series
Connection pitch	35 mm
[I _{cw}] rated short-time withstand current	1,8 KA 30 s IEC 60947-3 2,2 KA 20 s IEC 60947-3 4,9 KA 3 s IEC 60947-3 8,5 KA 1 s IEC 60947-3
Augstums	136 mm
Platums	295 mm
Dziļums	131 mm
Neto svars	6,4 kg

Vide

Standarti	IEC 60947-1 IEC 60947-3
Produkta sertifikācija	CB
Aizsardzības klase pret elektriskās strāvas triecienu	II klase
IP aizsardzības pakāpe	IP40 atbilst IEC 60947-3
Pollution degree	3
Apkārtējā gaisa temperatūra darbībai	-25...70 °C
Apkārtējā gaisa temperatūra uzglabāšanai	-50...85 °C

Iepakojšanas vienības

Pirmā iepakojuma vienības tips	PCE
Vienību skaits 1. iepakojumā	1
1. iepakojuma augstums	18,0 cm
1. iepakojuma platums	17,0 cm
1. iepakojuma garums	40,0 cm
1. iepakojuma svars	6,39 kg
Otrā iepakojuma vienības tips	S04
Vienību skaits 2. iepakojumā	2
2. iepakojuma augstums	30,0 cm
2. iepakojuma platums	40,0 cm
2. iepakojuma garums	60,0 cm
2. iepakojuma svars	13,546 kg

Piedāvājiēt ilgtspēju

Ilgtspējīgs piedāvājuma statuss	Green Premium izstrādājums
REACH regula	 REACH Deklarācija
ES RoHS direktīva	Atbilst izņēmumiem
Nesatur dzīvsudrabu	Jā
Ķīnas RoHS regula	 Ķīnas RoHS Deklarācija
Informācija par RoHS izņēmumiem	 Jā
Vides informācijas publicēšana	 Produkta Ietekme Uz Vidi
Cirkularitātes profils	 Informācija Par Eksploatācijas Izbeigšanu
WEEE	Eiropas Savienības tirgū no šī produkta ir jāatbrīvojas, ievērojot noteiktu atkritumu savākšanas kārtību, un produkts nedrīkst nonākt sadzīves atkritumu tvertnēs.

Līguma garantija

Garantija

18 months
