

SXWASB24X10001

Automation server, SpaceLogic Plant Room Servers, AS-B-24, 24 I/O points, BACnet, MS/TP, modbus



Galvenā

Ierīces īsais nosaukums	AS-B-24
Produkta vai sastāvdaļas veids	Controller system
Komunikācijas pakalpojums	Modbus TCP server Modbus TCP client SMTPS e-mail notification SNMP network management SMTP e-mail notification
Produkta sertifikācija	ICES-003[RETURN]BTL[RETURN]FCC 15. daļa B klase[RETURN]cULus[RETURN]CE[RETURN]RCM
Platums	198 mm
Enerģijas patēriņš W	10 W
Power consumption in VA	15 VA
Tīkla frekvence	50 Hz 60 Hz
Ekrāna tips	FSTN transfective LCD
Clock drift	+/- 52 s/month
Ekrāna izšķirtspēja	128 x 64 pixels
IP aizsardzības pakāpe	IP20
Apkārtējā gaisa temperatūra uzglabāšanai	-20...70 °C
Ambient air temperature for operation	0...50 °C
Input/output type	16 universal I/O
Relatīvais mitrums	0...95 % nekondensējošs
Memory type	256 MB FRAM 2 GB flash
[Us] rated supply voltage	19...29 V AC 21...33 V DC
Number of inputs	4 digital
Izeju skaits	4 relay
Augstums	114 mm
Produkta svars	5,04 kg
Dziļums	64 mm
Number of port	2 ETHERNET
Diapazons	EcoStruxure Building Operation

The information provided in this documentation contains general descriptions and/or technical characteristics of the performance of the products contained herein. This documentation is not intended as a substitute for and is not to be used for determining suitability or reliability of these products for specific user applications. It is the duty of any such user or integrator to perform the appropriate and complete risk analysis, evaluation and testing of the products with respect to the relevant specific application or use thereof. Neither Schneider Electric Industries SAS nor any of its affiliates or subsidiaries shall be responsible or liable for misuse of the information contained herein.

Papildinošs

Produktu saderība	Xenta I/NET Continuum Balco Satchwell Honeywell Johnson Control
Produkta zīmols	Schneider Electric
Switching frequency	25 Hz
Web services	TLS 1.0 Programmable scripts : alarm summaries, report management HTTP server
Ekrāna krāsa	Monochrome
Montāžas stiprinājums	DIN sliede
Flame retardance	UL94V0-5VB
Electrical connection	Plug-in sub-base Terminal with a manual override switch
Supply	Power supply 24 V, <0,5 A
Integrated connection type	USB 2.0 type A USB type mini B Ethernet RJ45 Serial link RS485
Analogue input type	Configurable voltage, current or probe 0...20 mA Configurable voltage, current or probe 0...10 V input voltage Configurable voltage, current or probe 20 kOhm connection of probes Configurable voltage, current or probe 10 kOhm connection of probes Configurable voltage, current or probe 2.2 kOhm connection of probes Configurable voltage, current or probe 1.8 kOhm connection of probes Configurable voltage, current or probe 1 kOhm connection of probes Configurable voltage, current or probe 10 kOhm with shunt
Display type	FSTN transfective LCD 36 x 17 mm
Communication port protocol	BACnet Modbus TCP master RS485 Modbus TCP slave RS485 HTTPS RJ45 HTTP RJ45
Realtime clock	With
Processor name	Spear 320s
Standards	UL 916 FCC CFR 47 part 15
Materiāls	ABS/PC

Vide

Temperature probe type	LG-Ni 1000 - 50...150 °C Ni 1000 - 50...150 °C Pt 1000 - 50...150 °C
------------------------	--

Iepakojšanas vienības

Pirmā iepakojuma vienības tips	PCE
Vienību skaits 1. iepakojumā	1
1. iepakojuma augstums	6,8 cm
1. iepakojuma platums	11,5 cm
1. iepakojuma garums	20,0 cm
1. iepakojuma svars	460,0 g
Otrā iepakojuma vienības tips	S03
Vienību skaits 2. iepakojumā	12
2. iepakojuma augstums	30,0 cm
2. iepakojuma platums	30,0 cm
2. iepakojuma garums	40,0 cm
2. iepakojuma svars	6,281 kg

Piedāvājiēt ilgtspēju

Ilgspējīgs piedāvājuma statuss	Green Premium izstrādājums
REACH regula	REACH Deklarācija
ES RoHS direktīva	Atbilst izņēmumiem
Nesatur dzīvsudrabu	Jā
Ķīnas RoHS regula	Ķīnas RoHS Deklarācija
Informācija par RoHS izņēmumiem	Jā
Vides informācijas publiskošana	Produkta Ietekme Uz Vidi
Cirkularitātes profils	Informācija Par Eksploatācijas Izbeigšanu
WEEE	Eiropas Savienības tirgū no šī produkta ir jāatbrīvojas, ievērojot noteiktu atkritumu savākšanas kārtību, un produkts nedrīkst nonākt sadzīves atkritumu tvertnēs.
Nesatur PVH	Jā
Halogēnu satura veiktspēja	Produkta plastmasas detaļas un kabeļi nesatur halogēnus