

XVUC23

Modular tower light, Harmony XVU, illuminated LED units, green, 60mm, steady, IP65, 24V AC DC



Galvenā

| | |
|-------------------------------------|--|
| Produkta sērija | Harmony XVU |
| Produkta vai sastāvdaļas veids | Modular tower light |
| Bākas vai indikatoru vienības veids | LED unit |
| Mounting diameter | 60 mm |
| Component name | XVU |
| Gaismas avots | LED, zaļš |
| Ierīces pielietojums | Automotive Packaging machine Machine tools |

Papildinošs

| | |
|--------------------------------|---|
| Signāla veids | Steady |
| Assembly style | Customer assembly, up to 5 units Up to 4 units with buzzer |
| Material | PC (polikarbonāts) V-2 UL 94 PC (polikarbonāts) V-0 UL 94 |
| [Us] rated supply voltage | 24 V AC/DC |
| Maximum power dissipation in W | 2,5 W |
| Current consumption | <= 50 mA |
| Signalling type | Steady |
| Garums | 50 mm |
| Neto svars | 0,064 kg |

Vide

| | |
|--|-------------------------|
| Produkta sertifikācija | CSA[RETURN]UL[RETURN]CE |
| Apkārtējā gaisa temperatūra uzglabāšanai | -40...70 °C |
| IP degree of protection | IP65 |
| Apkārtējā gaisa temperatūra darbībai | -25...50 °C |
| Vibration resistance | 2 gn |

Iepakojšanas vienības

| | |
|--------------------------------|---------|
| Pirmā iepakojuma vienības tips | PCE |
| Vienību skaits 1. iepakojumā | 1 |
| 1. iepakojuma augstums | 9 cm |
| 1. iepakojuma platums | 13,3 cm |
| 1. iepakojuma garums | 9,1 cm |
| 1. iepakojuma svars | 145 g |
| Otrā iepakojuma vienības tips | S03 |
| Vienību skaits 2. iepakojumā | 24 |
| 2. iepakojuma augstums | 30 cm |
| 2. iepakojuma platums | 30 cm |
| 2. iepakojuma garums | 40 cm |
| 2. iepakojuma svars | 4,04 kg |

| | |
|--------------------------------|----------|
| Trešā iepakojuma vienības tips | PAL |
| Vienību skaits 3. iepakojumā | 192 |
| 3. iepakojuma augstums | 60 cm |
| 3. iepakojuma platums | 80 cm |
| 3. iepakojuma garums | 70 cm |
| 3. iepakojuma svars | 35,84 kg |


Piedāvājiēt ilgtspēju

| | |
|---------------------------------|--|
| Ilgtspējīgs piedāvājuma statuss | Green Premium izstrādājums |
| REACH regula | REACH Deklarācija |
| ES RoHS direktīva | Proaktīva atbilstība (uz izstrādājumu neattiecas ES RoHS juridiskās saistības) |
| Nesatur dzīvsudrabu | Jā |
| Ķīnas RoHS regula | Ķīnas RoHS Deklarācija |
| Informācija par RoHS izņēmumiem | Jā |
| Vides informācijas publicēšana | Produkta Ietekme Uz Vidi |
| Cirkularitātes profils | Informācija Par Eksploatācijas Izbeigšanu |

Illuminated LED Unit

Dimensions

$\frac{\text{mm}}{\text{in.}}$



Modular Tower Lights Mounting



| Drawing | Part number | Part name |
|----------|----------------------|------------------------------|
| A1 | - | Top cover |
| - | Top cover (Silver) | |
| A2 | XVUC9S | Buzzer unit |
| XVUC9SQ | Buzzer unit (Silver) | |
| A3 | XVUC23 | Green LED unit |
| XVUC24 | Red LED unit | |
| XVUC25 | Orange LED unit | |
| XVUC26 | Blue LED unit | |
| XVUC27 | White LED unit | |
| XVUC28 | Yellow LED unit | |
| A4 | XVUC29 | Multi-LED unit |
| A5 | XVUC29P | Multi-LED unit, Pulse signal |
| A6 | XVUC9V | Sound unit |
| A7 | XVUC9VP | Sound unit, Pulse signal |
| A8 | XVUC020 | Extender |
| XVUC020Q | Extender (Silver) | |
| A9 | XVUC21B | DC body |

| Drawing | Part number | Part name |
|-----------|--|---|
| XVUC21BQ | DC body (Silver) | |
| A10 | XVUC21M | AC body NPN |
| XVUC21MP | AC body PNP | |
| XVUC21MQP | AC body PNP (Silver) | |
| A11 | XVUZ06 | Flexible option |
| A12 | XVUZ01 | Fixing Unit - Direct mounting (3 pins) |
| XVUZ01Q | Fixing Unit - Direct mounting (Silver,3 pins) | |
| XVUZ03 | Fixing Unit - Direct mounting (2 pins) | |
| XVUZ04 | Fixing Unit - Direct mounting (4 pins) | |
| A13 | XVUZ02 | Fixing Unit - Plate with Pole (100 mm) |
| XVUZ02Q | Fixing Unit - Plate with Pole (100 mm, Silver) | |
| XVUZ400 | Fixing Unit - Plate with Pole (400 mm) | |
| XVUZ800 | Fixing Unit - Plate with Pole (800 mm) | |
| A14 | XVUZ05 | Fixing Unit - Plate with adjustment pole (100-385 mm) |
| A15 | XVUC43 | Green LED unit, Flash |
| XVUC44 | Red LED unit, Flash | |
| XVUC45 | Orange LED unit, Flash | |
| XVUC46 | Blue LED unit, Flash | |
| XVUC47 | White LED unit, Flash | |
| XVUC48 | Yellow LED unit, Flash | |
| A16 | XVUZ100T | Fixing Unit - Metal bracket with pole (100 mm) |
| XVUZ250T | Fixing Unit - Metal bracket with pole(250 mm) | |
| XVUZ400T | Fixing Unit - Metal bracket with pole (400 mm) | |
| A17 | XVUZ12 | Fixing plate for use on vertical support - black |

Illuminated Units, Multi-LED and Audible Units Wiring



- (A) Fixing Unit
 - (1) Dimensions of Wiring size
 - (2) Push-in Wire Connectors
 - (3) Fuse : 2A ,250V
 - (4) Fuse : 0.5A ,125V
 - (5) Modular Tower Lights 24V AC/DC
 - (6) Modular Tower Lights 100...240V AC
- L1 to Illuminated LED Units
L5 :