



Galvenā

Diapazons	MasterPact
Produkta vai sastāvdaļas veids	Application
Application description	Trip fault WFC
Saderība ar	MasterPact MTZ1 circuit breaker MasterPact MTZ2 circuit breaker MasterPact MTZ3 circuit breaker
Product compatibility	Control unit MicroLogic 2.0 X Control unit MicroLogic 3.0 X Control unit MicroLogic 5.0 X Control unit MicroLogic 6.0 X Control unit MicroLogic 7.0 X Control unit MicroLogic 2.0 Xi Control unit MicroLogic 3.0 Xi Control unit MicroLogic 5.0 Xi Control unit MicroLogic 6.0 Xi Control unit MicroLogic 7.0 Xi
Servisa pakalpojuma apraksts	Sampling period of 512 micro seconds in case of trip of LSI or G protection Allows to log automatically five cycles of phase and neutral currents Records the following status: circuit breaker open/closed/trip and ZSI signals Display one cycle before the fault and 4 cycles after
Servisa pakalpojuma ieguvumi	Help to understand the potential damage on the installation Support analysis of global behaviour of the circuit breaker in the power system Help to understand the nature and gravity of the fault (amplitude and duration)
Energy management	Diagnostics and maintenance ,crisis management (option)

Papildinošs

Programmatūras nosaukums	EcoStruxure Power Commission
--------------------------	------------------------------

Iepakojšanas vienības

Pirmā iepakojuma vienības tips	PCE
Vienību skaits 1. iepakojumā	1
1. iepakojuma svars	0,001 g

Piedāvājiem ilgtspēju

REACH regula	REACH Deklarācija
ES RoHS direktīva	Atbilst izņēmumiem
Nesatur dzīvsudrabu	Jā
Ķīnas RoHS regula	Ķīnas RoHS Deklarācija
Informācija par RoHS izņēmumiem	Jā