

# 8800210030

SpaceLogic M310 Actuator for Globe Valves,  
Multi-Signal Control, Non-Spring Return,  
24Vac/dc, Terminal Block Connection, 300N,  
Linear, IP54



## Galvenā

Actuator product range	SpaceLogic
Produkta vai sastāvdaļas veids	Actuator
Actuator type	Electric
Actuator product series	M310
Actuator model	M310
Produkta mērķa pielietojums	Globe valve
Aktuātors	Linear
Motor type	Brushless DC motor
Vadības veids	Automatic reset
Switch function	2 SPDT (nav obligāti)
Rated supply voltage	24 V AC/DC
Analogue input range	0...10 V DC
Feedback signal	2...10 V DC
Transformer rated power in VA	30 VA
Power consumption in VA	6 VA AC
Hold-in power consumption in VA	6 VA AC
Power loss return	Non-spring return
Control signal	Floating Proportional/modulating
Stroke length	9...32 mm
Stroke auto calibration	"True"
Elektroizolācijas klase	II klase
Force N	300 N
Force lbf	68 lbf
Position indicator	Stroke indicator on yoke
Conduit connection	3 x M20 Gland for 6-9 mm O/D cable
Leads and connections	Terminal block
Stroke running time	15 s
IP aizsardzības pakāpe	IP54
Darba cikls	20 %
Apkārtējā gaisa temperatūra darbībai	-10...50 °C
Relative humidity	0...90 %
Apkārtējā gaisa temperatūra uzglabāšanai	-10...50 °C
Targeted region	Europe Asia Pacific. Australia.

The information provided in this documentation contains general descriptions and/or technical characteristics of the performance of the products contained herein. This documentation is not intended as a substitute for and is not to be used for determining suitability or reliability of these products for specific user applications. It is the duty of any such user or integrator to perform the appropriate and complete risk analysis, evaluation and testing of the products with respect to the relevant specific application or use thereof. Neither Schneider Electric Industries SAS nor any of its affiliates or subsidiaries shall be responsible or liable for misuse of the information contained herein.

## Iepakojšanas vienības

Pirmā iepakojuma vienības tips	PCE
Vienību skaits 1. iepakojumā	1
1. iepakojuma augstums	18,0 cm
1. iepakojuma platums	13,2 cm
1. iepakojuma garums	25,5 cm
1. iepakojuma svars	1,897 kg

## Piedāvājiem ilgtspēju

REACH regula	<a href="#">REACH Deklarācija</a>
ES RoHS direktīva	Atbilst izņēmumiem
Nesatur dzīvsudrabu	Jā
Ķīnas RoHS regula	<a href="#">Ķīnas RoHS Deklarācija</a>
Informācija par RoHS izņēmumiem	<a href="#">Jā</a>
Cirkularitātes profils	<a href="#">Informācija Par Eksploatācijas Izbeigšanu</a>
WEEE	Eiropas Savienības tirgū no šī produkta ir jāatbrīvojas, ievērojot noteiktu atkritumu savākšanas kārtību, un produkts nedrīkst nonākt sadzīves atkritumu tvertnēs.