



Galvenā

Range	TeSys
Product Name	TeSys VARIO
Device Short Name	VCF
Product Type	Emergency stop switch disconnecter

Papildinošs

Device Composition	Switch Handle
Mounting Support	Handle durvis Slēdzis durvis
Mounting Method	By 4 screws handle
Performance Level	High performance
Number of Poles	3P
Contact Type and Composition	3 NO
[Ue] IEC Rated Operational Voltage	690 V AC 50/60 Hz
IEC Rated Operational Power in W	11 KW 500 V AC-23A) 11 KW 690 V AC-3) 15 KW 690 V AC-23A) 4 KW 230...240 V AC-3) 5,5 KW 400...415 V AC-3) 7,5 KW 500 V AC-3) 5,5 KW 230...240 V AC-23A) 7,5 KW 400...415 V AC-23A)
[Ie] Rated Operational Current	14,5 A AC-23 Ue: 400 V
[Ith] Conventional Free Air Thermal Current	25 A
[Ithe] Conventional Enclosed Thermal Current	20 A
Making Capacity (I Rms)	250 A 400 V AC-21A 250 A 400 V AC-22A 250 A 400 V AC-23A
Breaking Capacity	200 A 400 V AC-21A) 200 A 400 V AC-22A) 200 A 400 V AC-23A)
Rated Conditional Short Circuit Current	10 KA 400 V 25 A aM 10 kA 400 V 25 A gG
[Icm] Rated Short Circuit Making Capacity	1 kA 400 V at Ipeak
[Icw] Rated Short Time Withstand Current	300 A 400 V 1 s
[Uimp] Rated Impulse Withstand Voltage	8 kV
Suitability for Isolation	Yes
Network Type	AC DC
Intermittent Duty Class	30
Control Type	Rotary handle

Rotary Handle Mounting Style	Direct
Handle Color	Red
Handle Front Plate Color	Yellow
Rotary Handle Padlocking	1 to 3 padlocks 4...8 mm
Marking	0 - 1
Mechanical Durability	100000 cikli
Electrical Durability	100000 Cikli AC-21 30000 cikli DC-1...5
IEC Terminal Connection	Strāvas ķēde screw clamp terminals 10 mm ² ciets Strāvas ķēde screw clamp terminals 6 mm ² elastīgs - with cable end
Tightening Torque	Strāvas ķēde 2,1 N.m screw clamp terminals
Base Dimension	60 x 60 mm
Height	74 mm
Width	60 mm
Product Weight	0,25 kg



Vide



Standards	IEC 60947-3
Product Certifications	CSA[RETURN]CCC[RETURN]GL[RETURN]UL[RETURN]UKCA
Degree of Protection	IP20 atbilst IEC 60529 IP65
Protective Treatment	TC
Mechanical Robustness	Vibrations 10...150 Hz 1 gn) IEC 60068-2-6 Shocks 11 ms 30 Gn) IEC 60068-2-27
Ambient Air Temperature for Operation	-20...50 °C
Fire Resistance	960 °C IEC 60695-2-1
Compatibility Code	Main switch disconnecter

Iepakojšanas vienības

Pirmā iepakojuma vienības tips	PCE
Vienību skaits 1. iepakojumā	1
1. iepakojuma augstums	8,000 cm
1. iepakojuma platums	8,500 cm
1. iepakojuma garums	12,000 cm
1. iepakojuma svars	219,000 g
Otrā iepakojuma vienības tips	S03
Vienību skaits 2. iepakojumā	24
2. iepakojuma augstums	30,000 cm
2. iepakojuma platums	30,000 cm
2. iepakojuma garums	40,000 cm
2. iepakojuma svars	5,669 kg
Trešā iepakojuma vienības tips	P06
Vienību skaits 3. iepakojumā	192
3. iepakojuma augstums	75,000 cm
3. iepakojuma platums	80,000 cm
3. iepakojuma garums	60,000 cm
3. iepakojuma svars	53,352 kg

Piedāvājiēt ilgtspēju

Ilgtspējīgs piedāvājuma statuss	Green Premium izstrādājums
REACH regula	
ES RoHS direktīva	Atbilst izņēmumiem
Nesatur toksiskus smagos metālus	Jā
Nesatur dzīvsudrabu	Jā
Ķīnas RoHS regula	

Informācija par RoHS izņēmumiem	 Jā
Vides informācijas publicēšana	 Produkta letekme Uz Vidi
Cirkularitātes profils	Nav jāveic īpašas darbības, lai nodotu otrreizējai pārstrādei
WEEE	Eiropas Savienības tirgū no šī produkta ir jāatbrīvojas, ievērojot noteiktu atkritumu savākšanas kārtību, un produkts nedrīkst nonākt sadzīves atkritumu tvertnēs.
Nesatur PVH	Jā
Halogēnu satura veiktspēja	Halogēnus nesaturošs produkts

Līguma garantija

Garantija	18 months
-----------	-----------