

# LC1D098P7

Contacteur, TeSys Deca, 4P(2NO+2NC), AC-1, <=440V, 20A, 230VAC 50/60Hz coil, screw clamp terminal



## Galvenā

Produkta sērija	TeSys Deca
Produkta vai sastāvdaļas veids	Contacteur
Ierīces īsais nosaukums	LC1D
Contacteur application	Resistive load
Utilisation category	AC-1 AC-3 AC-3e AC-4
Polu skaits	4P
[Ue] nominālais darbības spriegums	Strāvas ķēde: <= 690 V AC 25...400 Hz Strāvas ķēde: <= 250 V DC
[Ie] rated operational current	20 A (at <60 °C) at <= 440 V AC AC-1 for strāvas ķēde
[Uc] control circuit voltage	230 V AC 50/60 Hz

## Papildinošs

Compatibility code	LC1D
Pole contact composition	2 NO + 2 NC
Protective cover	With
[Ith] conventional free air thermal current	20 A (at 60 °C) for strāvas ķēde 10 A (at 60 °C) for signalling circuit
Irms rated making capacity	250 A at 440 V for strāvas ķēde conforming to IEC 60947 140 A AC for signalling circuit conforming to IEC 60947-5-1 250 A DC for signalling circuit conforming to IEC 60947-5-1
Rated breaking capacity	250 A at 440 V for strāvas ķēde conforming to IEC 60947
[Icw] rated short-time withstand current	105 A 40 °C - 10 s for strāvas ķēde 210 A 40 °C - 1 s for strāvas ķēde 30 A 40 °C - 10 min for strāvas ķēde 61 A 40 °C - 1 min for strāvas ķēde 100 A - 1 s for signalling circuit 120 A - 500 ms for signalling circuit 140 A - 100 ms for signalling circuit
Associated fuse rating	10 A gG for signalling circuit conforming to IEC 60947-5-1 25 A gG at <= 690 V coordination type 1 for strāvas ķēde 20 A gG at <= 690 V coordination type 2 for strāvas ķēde
Average impedance	2,5 mhm - Ith 25 A 50 Hz for strāvas ķēde
Power dissipation per pole	1,56 W AC-1
[Ui] rated insulation voltage	Strāvas ķēde 690 V IEC 60947-4-1 Strāvas ķēde 600 V CSA Strāvas ķēde 600 V UL Signalling circuit 690 V IEC 60947-1 Signalling circuit 600 V CSA Signalling circuit 600 V UL
Pārsprieguma kategorija	III
Piesārņojuma pakāpe	3
[Uimp] rated impulse withstand voltage	6 kV IEC 60947
Safety reliability level	B10d = 1369863 cikli contacteur with nominal load EN/ISO 13849-1 B10d = 20000000 cikli contacteur with mechanical load EN/ISO 13849-1
Mehāniskā izturība	15 M cikli
Electrical durability	0,3 M cikli 20 A AC-1 <= 690 V

The information provided in this documentation contains general descriptions and/or technical characteristics of the performance of the products contained herein. This documentation is not intended as a substitute for and is not to be used for determining suitability or reliability of these products for specific user applications. It is the duty of any such user or integrator to perform the appropriate and complete risk analysis, evaluation and testing of the products with respect to the relevant specific application or use thereof. Neither Schneider Electric Industries SAS nor any of its affiliates or subsidiaries shall be responsible or liable for misuse of the information contained herein.

Control circuit type	AC 50/60 Hz
Coil technology	Without built-in suppressor module
Control circuit voltage limits	0.3...0.6 U <sub>c</sub> -40...60 °C drop-out AC 50/60 Hz 0.8...1.1 U <sub>c</sub> -40...60 °C operational AC 50 Hz 0.85...1.1 U <sub>c</sub> -40...60 °C operational AC 60 Hz
Inrush power in VA	70 VA 60 Hz cos phi 0,75 (at 20 °C) 70 VA 50 Hz cos phi 0,75 (at 20 °C)
Hold-in power consumption in VA	7,5 VA 60 Hz cos phi 0,3 (at 20 °C) 7 VA 50 Hz cos phi 0,3 (at 20 °C)
Heat dissipation	2...3 W at 50/60 Hz
Operating time	12...22 ms closing 4...19 ms opening
Maximum operating rate	3600 cikls/h 60 °C
Connections - terminals	Strāvas ķēde: screw clamp terminals 1 1...4 mm <sup>2</sup> - cable stiffness: elastīgs without cable end Strāvas ķēde: screw clamp terminals 2 1...4 mm <sup>2</sup> - cable stiffness: elastīgs without cable end Strāvas ķēde: screw clamp terminals 1 1...4 mm <sup>2</sup> - cable stiffness: elastīgs with cable end Strāvas ķēde: screw clamp terminals 2 1...2,5 mm <sup>2</sup> - cable stiffness: elastīgs with cable end Strāvas ķēde: screw clamp terminals 1 1...4 mm <sup>2</sup> - cable stiffness: ciets without cable end Strāvas ķēde: screw clamp terminals 2 1...4 mm <sup>2</sup> - cable stiffness: ciets without cable end Control circuit: screw clamp terminals 1 1...4 mm <sup>2</sup> - cable stiffness: elastīgs without cable end Control circuit: screw clamp terminals 2 1...4 mm <sup>2</sup> - cable stiffness: elastīgs without cable end Control circuit: screw clamp terminals 1 1...4 mm <sup>2</sup> - cable stiffness: elastīgs with cable end Control circuit: screw clamp terminals 2 1...2,5 mm <sup>2</sup> - cable stiffness: elastīgs with cable end Control circuit: screw clamp terminals 1 1...4 mm <sup>2</sup> - cable stiffness: ciets without cable end Control circuit: screw clamp terminals 2 1...4 mm <sup>2</sup> - cable stiffness: ciets without cable end
Tightening torque	Strāvas ķēde 1,7 N.m screw clamp terminals flat Ø 6 mm Strāvas ķēde 1,7 N.m screw clamp terminals Philips No 2 Control circuit 1,7 N.m screw clamp terminals flat Ø 6 mm Control circuit 1,7 N.m screw clamp terminals Philips No 2 Control circuit 1,7 N.m screw clamp terminals pozidriv No 2 Strāvas ķēde 1,7 N.m screw clamp terminals pozidriv No 2
Papildkontakta veids	1 NO + 1 NC
Auxiliary contacts type	Mechanically linked 1 NO + 1 NC IEC 60947-5-1 Mirror contact 1 NC IEC 60947-4-1
Signalling circuit frequency	25...400 Hz
Minimum switching voltage	17 V for signalling circuit
Minimum switching current	5 mA for signalling circuit
Insulation resistance	> 10 MOhm for signalling circuit
Non-overlap time	1,5 Ms on de-energisation between NC and NO contact 1,5 ms on energisation between NC and NO contact
Montāžas stiprinājums	Plāksne Rail



## Vide

Standards	CSA C22.2 No 60947-4-1 EN 60947-4-1 EN 60947-5-1 IEC 60947-4-1 IEC 60947-5-1 UL 60947-5-1 UL 60947-4-1 CSA C22.2 No 60947-5-1 GB/T 14048.4
Produkta sertifikācija	UL[RETURN]CCC[RETURN]CSA[RETURN]UKCA[RETURN]EAC[RETURN]CB[RETURN]EU-RO-MR by DNV-GL
IP degree of protection	IP20 priekšpuse IEC&nbsp;60529
Protective treatment	THIEC 60068-2-30
Climatic withstand	IACS E10 exposure to damp heat IEC 60947-1 Annex Q category D exposure to damp heat
Permissible ambient air temperature around the device	-40...60 °C 60...70 °C with derating
Operating altitude	0...3000 m
Fire resistance	850 °C IEC 60695-2-1
Flame retardance	V1 UL 94
Mechanical robustness	Vibrations contactor open 2 Gn, 5...300 Hz) Vibrations contactor closed 4 Gn, 5...300 Hz) Shocks contactor open 10 Gn for 11 ms) Shocks contactor closed 15 Gn for 11 ms)
Augstums	85 mm
Platums	45 mm
Dziļums	92 mm
Neto svars	0,365 kg

## Iepakojšanas vienības

Pirmā iepakojuma vienības tips	PCE
Vienību skaits 1. iepakojumā	1
1. iepakojuma augstums	5,700 cm
1. iepakojuma platums	9,500 cm
1. iepakojuma garums	12,000 cm
1. iepakojuma svars	393,000 g
Otrā iepakojuma vienības tips	S02
Vienību skaits 2. iepakojumā	16
2. iepakojuma augstums	15,000 cm
2. iepakojuma platums	30,000 cm
2. iepakojuma garums	40,000 cm
2. iepakojuma svars	6,827 kg
Trešā iepakojuma vienības tips	P06
Vienību skaits 3. iepakojumā	256
3. iepakojuma augstums	75,000 cm
3. iepakojuma platums	60,000 cm
3. iepakojuma garums	80,000 cm
3. iepakojuma svars	117,232 kg

## Piedāvājiem ilgtspēju

Ilgspējīgs piedāvājuma statuss	Green Premium izstrādājums
REACH regula	 REACH Deklarācija
Nesatur REACH SVHC	Jā
ES RoHS direktīva	Atbilstīgs  ES RoHS Deklarācija
Nesatur toksiskus smagos metālus	Jā
Nesatur dzīvsudrabu	Jā

Ķīnas RoHS regula	<a href="#">Ķīnas RoHS Deklarācija</a>
Informācija par RoHS izņēmumiem	<a href="#">Jā</a>
Vides informācijas publicēšana	<a href="#">Produkta Ietekme Uz Vidi</a>
Cirkularitātes profils	<a href="#">Informācija Par Ekspluatācijas Izbeigšanu</a>
WEEE	Eiropas Savienības tirgū no šī produkta ir jāatbrīvojas, ievērojot noteiktu atkritumu savākšanas kārtību, un produkts nedrīkst nonākt sadzīves atkritumu tvertnēs.
Nesatur PVH	Jā

## Līguma garantija

Garantija	18 months
-----------	-----------