

LC1D093BL

Contacteur, TeSys Deca, 3P(3NO), AC-3/AC-3e, <=440V, 9A, 24V DC low consumption coil, spring terminals



Galvenā

Produkta sērija	TeSys Deca
Produkta vai sastāvdaļas veids	Contacteur
Ierīces īsais nosaukums	LC1D
Contacteur application	Resistive load Motor control
Utilisation category	AC-1 AC-3 AC-4 AC-3e
Polu skaits	3P
[Ue] nominālais darbības spriegums	Strāvas ķēde: <= 690 V AC 25...400 Hz Strāvas ķēde: <= 300 V DC
[Ie] rated operational current	9 A (at <60 °C) at <= 440 V AC AC-3 for strāvas ķēde 20 A (at <60 °C) at <= 440 V AC AC-1 for strāvas ķēde 9 A (at <60 °C) at <= 440 V AC AC-3e for strāvas ķēde
[Uc] control circuit voltage	24 V DC

Papildinošs

Motor power kW	2,2 kW at 220...230 V AC 50/60 Hz (AC-3) 4 kW at 380...400 V AC 50/60 Hz (AC-3) 4 kW at 415 V AC 50/60 Hz (AC-3) 4 kW at 440 V AC 50/60 Hz (AC-3) 5,5 kW at 500 V AC 50/60 Hz (AC-3) 5,5 kW at 660...690 V AC 50/60 Hz (AC-3) 2,2 kW at 220...230 V AC 50/60 Hz (AC-3e) 4 kW at 380...400 V AC 50/60 Hz (AC-3e) 4 kW at 415 V AC 50/60 Hz (AC-3e) 4 kW at 440 V AC 50/60 Hz (AC-3e) 5,5 kW at 500 V AC 50/60 Hz (AC-3e) 5,5 kW at 660...690 V AC 50/60 Hz (AC-3e) 2,2 kW at 400 V AC 50/60 Hz (AC-4)
Motor power hp	1 Hp at 230/240 V AC 50/60 Hz for 1 fāzes motors 2 Hp at 200/208 V AC 50/60 Hz for 3 fāzes motors 2 Hp at 230/240 V AC 50/60 Hz for 3 fāzes motors 5 Hp at 460/480 V AC 50/60 Hz for 3 fāzes motors 7,5 Hp at 575/600 V AC 50/60 Hz for 3 fāzes motors 0,33 hp at 115 V AC 50/60 Hz for 1 fāzes motors
Compatibility code	LC1D
Pole contact composition	3 NO
Protective cover	With
[Ith] conventional free air thermal current	10 A (at 60 °C) for signalling circuit 16 A (at 60 °C) for strāvas ķēde
Irms rated making capacity	250 A at 440 V for strāvas ķēde conforming to IEC 60947 140 A AC for signalling circuit conforming to IEC 60947-5-1 250 A DC for signalling circuit conforming to IEC 60947-5-1
Rated breaking capacity	250 A at 440 V for strāvas ķēde conforming to IEC 60947

The information provided in this documentation contains general descriptions and/or technical characteristics of the performance of the products contained herein. This documentation is not intended as a substitute for and is not to be used for determining suitability or reliability of these products for specific user applications. It is the duty of any such user or integrator to perform the appropriate and complete risk analysis, evaluation and testing of the products with respect to the relevant specific application or use thereof. Neither Schneider Electric Industries SAS nor any of its affiliates or subsidiaries shall be responsible or liable for misuse of the information contained herein.

[I _{cw}] rated short-time withstand current	105 A 40 °C - 10 s for strāvas ķēde 210 A 40 °C - 1 s for strāvas ķēde 30 A 40 °C - 10 min for strāvas ķēde 61 A 40 °C - 1 min for strāvas ķēde 100 A - 1 s for signalling circuit 120 A - 500 ms for signalling circuit 140 A - 100 ms for signalling circuit
Associated fuse rating	10 A gG for signalling circuit conforming to IEC 60947-5-1 25 A gG at ≤ 690 V coordination type 1 for strāvas ķēde 20 A gG at ≤ 690 V coordination type 2 for strāvas ķēde
Average impedance	2,5 mhm - I _{th} 16 A 50 Hz for strāvas ķēde
Power dissipation per pole	1,56 W AC-1 0,2 W AC-3 0,2 W AC-3e
[U _i] rated insulation voltage	Strāvas ķēde 690 V IEC 60947-4-1 Strāvas ķēde 600 V CSA Strāvas ķēde 600 V UL Signalling circuit 690 V IEC 60947-1 Signalling circuit 600 V CSA Signalling circuit 600 V UL
Pārsprieguma kategorija	III
Piesārņojuma pakāpe	3
[U _{imp}] rated impulse withstand voltage	6 kV IEC 60947
Safety reliability level	B10d = 1369863 cikli contactor with nominal load EN/ISO 13849-1 B10d = 20000000 cikli contactor with mechanical load EN/ISO 13849-1
Mehāniskā izturība	30 M cikli
Electrical durability	0,6 M cikli 25 A AC-1 ≤ 440 V 2 M cikli 9 A AC-3 ≤ 440 V 2 M cikli 9 A AC-3e ≤ 440 V
Control circuit type	DC low consumption
Coil technology	Built-in bidirectional peak limiting diode suppressor
Control circuit voltage limits	0.1...0.3 U _c -40...70 °C drop-out DC 0.8...1.25 U _c -40...60 °C operational DC 1...1.25 U _c 60...70 °C operational DC
Inrush power in W	2,4 W 20 °C)
Hold-in power consumption in W	2,4 W 20 °C
Operating time	77 ±15 % ms closing 25 ±20 % ms opening
Time constant	40 ms
Maximum operating rate	3600 cikls/h 60 °C
Connections - terminals	Strāvas ķēde: spring terminals 1 2,5 mm ² - cable stiffness: elastīgs without cable end Strāvas ķēde: spring terminals 2 2,5 mm ² - cable stiffness: elastīgs without cable end Control circuit: spring terminals 1 2,5 mm ² - cable stiffness: elastīgs without cable end Control circuit: spring terminals 2 2,5 mm ² - cable stiffness: elastīgs without cable end
Papildkontakta veids	1 NO + 1 NC
Auxiliary contacts type	Mechanically linked 1 NO + 1 NC IEC 60947-5-1 Mirror contact 1 NC IEC 60947-4-1
Signalling circuit frequency	25...400 Hz
Minimum switching voltage	17 V for signalling circuit
Minimum switching current	5 mA for signalling circuit
Insulation resistance	> 10 MOhm for signalling circuit
Non-overlap time	1,5 Ms on de-energisation between NC and NO contact 1,5 ms on energisation between NC and NO contact
Montāžas stiprinājums	Rail Plāksne

Vide

Standards	CSA C22.2 No 14 EN 60947-4-1 EN 60947-5-1 IEC 60947-4-1 IEC 60947-5-1 UL 508 IEC 60335-1
Produkta sertifikācija	UL[RETURN]GOST[RETURN]CSA[RETURN]CCC[RETURN]GL[RETURN]BV[RETURN]LROS (Lloyds register of shipping)[RETURN]DNV[RETURN]RINA[RETURN]UKCA
IP degree of protection	IP20 priekšpuse IEC 60529
Protective treatment	THIEC 60068-2-30
Climatic withstand	IACS E10 exposure to damp heat IEC 60947-1 Annex Q category D exposure to damp heat
Permissible ambient air temperature around the device	-40...60 °C 60...70 °C with derating
Operating altitude	0...3000 m
Fire resistance	850 °C IEC 60695-2-1
Flame retardance	V1 UL 94
Mechanical robustness	Vibrations contactor open 2 Gn, 5...300 Hz) Vibrations contactor closed 4 Gn, 5...300 Hz) Shocks contactor open 10 Gn for 11 ms) Shocks contactor closed 15 Gn for 11 ms)
Augstums	99 mm
Platums	45 mm
Dziļums	95 mm
Neto svars	0,48 kg

Iepakojšanas vienības

Pirmā iepakojuma vienības tips	PCE
Vienību skaits 1. iepakojumā	1
1. iepakojuma augstums	5,500 cm
1. iepakojuma platums	10,300 cm
1. iepakojuma garums	11,000 cm
1. iepakojuma svars	560,000 g
Otrā iepakojuma vienības tips	S02
Vienību skaits 2. iepakojumā	15
2. iepakojuma augstums	15,000 cm
2. iepakojuma platums	30,000 cm
2. iepakojuma garums	40,000 cm
2. iepakojuma svars	8,662 kg

Piedāvājiēt ilgtspēju

Ilgspējīgs piedāvājuma statuss	Green Premium izstrādājums
REACH regula	 REACH Deklarācija
ES RoHS direktīva	Atbilst izņēmumiem
Nesatur toksiskus smagos metālus	Jā
Nesatur dzīvsudrabu	Jā
Ķīnas RoHS regula	 Ķīnas RoHS Deklarācija
Informācija par RoHS izņēmumiem	 Jā
Vides informācijas publicēšana	 Produkta letekme Uz Vidi
Cirkularitātes profils	 Informācija Par Eksploatācijas Izbeigšanu
Nesatur PVH	Jā

Līguma garantija

Garantija	18 months
-----------	-----------