



Galvenā

Diapazons	TeSys TeSys Deca
Produkta nosaukums	TeSys Deca
Produkta vai sastāvdaļas veids	Auxiliary contact block
Ierīces īsais nosaukums	LADN
Saderība ar	TeSys Deca LC1D80/95 3P[RETURN]TeSys Deca LC1D80 4P[RETURN]TeSys Deca LC1D40008[RETURN]TeSys Deca LC1D65008[RETURN]TeSys F LC1F[RETURN]TeSys Deca LC1D115
Montāžas vieta	Priekšā
Pole contact composition	1 NC
Contacts operation	Instantaneous
[Ue] rated operational voltage	690 V AC 25...400 Hz
[Ie] rated operational current	6 A at 120 V AC-15 1,04 A at 690 V AC-15 0,55 A at 125 V DC-13 0,1 A at 600 V DC-13
[Ui] rated insulation voltage	690 V IEC 60947-5-1 600 V UL 600 V CSA
[Ith] conventional free air thermal current	10 A (at 60 °C)
Standarti	EN/IEC 60947-5-1 UL 60947-5-1 CSA C22.2 No 60947-5-1 GB/T 14048.5
Produkta sertifikācija	CB[RETURN]UL[RETURN]CSA[RETURN]CCC[RETURN]C[RE]

Papildinošs

Irms rated making capacity	140 A AC conforming to IEC 60947-5-1 250 A DC conforming to IEC 60947-5-1
Permissible short-time rating	100 A 1 s 120 A 500 ms 140 A 100 ms
Protection type	GG fuse 10 A
Mehāniskā izturība	30 M cikli
Minimum switching current	5 mA
Minimum switching voltage	17 V
Non-overlap time	1,5 Ms on de-energisation no overlap between NC and NO contact 1,5 ms on energisation no overlap between NC and NO contact
Insulation resistance	> 10 MOhm
Connections - terminals	Screw clamp terminals 1 1...4 mm ² elastīgs with cable end Screw clamp terminals 1 1...4 mm ² elastīgs without cable end Screw clamp terminals 2 1...4 mm ² elastīgs with cable end Screw clamp terminals 2 1...4 mm ² elastīgs without cable end Screw clamp terminals 1 1...4 mm ² stingrs without cable end Screw clamp terminals 2 1...4 mm ² stingrs without cable end
Tightening torque	1,7 N.M flat Ø 6 mm 1,7 N.M Philips No 2 1,7 N.m pozidriv No 2

The information provided in this documentation contains general descriptions and/or technical characteristics of the products contained herein. This documentation is not intended as a substitute for and is not to be used for determining suitability or reliability of these products for specific user applications. It is the duty of any such user or integrator to perform the appropriate and complete risk analysis, evaluation and testing of the products with respect to the relevant specific application or use thereof. Neither Schneider Electric Industries SAS nor any of its affiliates or subsidiaries shall be responsible or liable for any misuse of the information contained herein.

Augstums	48 mm
Platums	13 mm
Dziļums	35 mm
Neto svars	0,02 kg
Krāsa	Tumši pelēks

Vide

Vides raksturlielumi	Normālu vidi
IP aizsardzības pakāpe	IP20 atbilst IEC 60529
Protective treatment	TH IEC 60068
Apkārtējā gaisa temperatūra uzglabāšanai	-60...80 °C
Apkārtējā gaisa temperatūra darbībai	-5...60 °C
Operating altitude	3000 m

Iepakojšanas vienības

Pirmā iepakojuma vienības tips	PCE
Vienību skaits 1. iepakojumā	1
1. iepakojuma augstums	5,1 cm
1. iepakojuma platums	4,2 cm
1. iepakojuma garums	2,7 cm
1. iepakojuma svars	20,0 g
Otrā iepakojuma vienības tips	S01
Vienību skaits 2. iepakojumā	84
2. iepakojuma augstums	15,0 cm
2. iepakojuma platums	15,0 cm
2. iepakojuma garums	40,0 cm
2. iepakojuma svars	1,772 kg

Piedāvājam ilgtspēju

Ilgspējīgs piedāvājuma statuss	Green Premium izstrādājums
REACH regula	REACH Deklarācija
Nesatur REACH SVHC	Jā
ES RoHS direktīva	Atbilstīgs ES RoHS Deklarācija
Nesatur toksiskus smagos metālus	Jā
Nesatur dzīvsudrabu	Jā
Ķīnas RoHS regula	Ķīnas RoHS Deklarācija
Informācija par RoHS izņēmumiem	Jā
Vides informācijas publiskošana	Produkta Ietekme Uz Vidi
Cirkularitātes profils	Nav jāveic īpašas darbības, lai nodotu otrreizējai pārstrādei
WEEE	Eiropas Savienības tirgū no šī produkta ir jāatbrīvojas, ievērojot noteiktu atkritumu savākšanas kārtību, un produkts nedrīkst nonākt sadzīves atkritumu tvertnēs.