





Galvenā

| | |
|---|--|
| Diapazons | TeSys |
| Produkta nosaukums | TeSys K |
| Produkta vai sastāvdaļas veids | Reversing contactor |
| Ierīces īsais nosaukums | LC2K |
| Ierīces pielietojums | Kontrolē |
| Contactor application | Motor control Resistive load |
| Utilisation category | AC-3 AC-3e AC-4 AC-1 |
| Ierīces komplektācija | Preassembled with reversing power busbar |
| Polu skaits | 3P |
| Power pole contact composition | 3 NO |
| [Ue] nominālais darbības spriegums | Strāvas ķēde: 690 V AC 50/60 Hz Signalling circuit: ≤ 690 V AC 50/60 Hz |
| [Ie] rated operational current | 9 A (at <60 °C) at ≤ 440 V AC AC-3 for strāvas ķēde 9 A (at <60 °C) at ≤ 440 V AC AC-3e for strāvas ķēde 20 A (at <60 °C) at ≤ 690 V AC AC-1 for strāvas ķēde |
| Motor power kW | 2,2 KW 220...230 V AC 50/60 Hz 4 KW 380...415 V AC 50/60 Hz 4 kW 440/690 V AC 50/60 Hz |
| Control circuit type | AC 50/60 Hz |
| [Uc] control circuit voltage | 230 V AC 50/60 Hz |
| Papildkontakta veids | 1 NO |
| [Uimp] rated impulse withstand voltage | 8 kV |
| Pārsprieguma kategorija | III |
| [Ith] conventional free air thermal current | 20 A (at 60 °C) for strāvas ķēde 10 A (at 50 °C) for signalling circuit |
| Irms rated making capacity | 110 A AC for strāvas ķēde conforming to IEC 60947 110 A AC for signalling circuit conforming to IEC 60947 |
| Rated breaking capacity | 110 A at 220...230 V conforming to IEC 60947 110 A at 380...400 V conforming to IEC 60947 110 A at 415 V conforming to IEC 60947 110 A at 440 V conforming to IEC 60947 80 A at 500 V conforming to IEC 60947 70 A at 660...690 V conforming to IEC 60947 |
| [Icw] rated short-time withstand current | 90 A 50 °C - 1 s for strāvas ķēde 85 A 50 °C - 5 s for strāvas ķēde 80 A 50 °C - 10 s for strāvas ķēde 60 A 50 °C - 30 s for strāvas ķēde 45 A 50 °C - 1 min for strāvas ķēde 40 A 50 °C - 3 min for strāvas ķēde 20 A 50 °C - ≥ 15 min for strāvas ķēde 80 A - 1 s for signalling circuit 90 A - 500 ms for signalling circuit 110 A - 100 ms for signalling circuit |
| Associated fuse rating | 25 A gG at ≤ 440 V for strāvas ķēde 25 A aM for strāvas ķēde 10 A gG for signalling circuit conforming to IEC 60947 10 A gG for signalling circuit conforming to VDE 0660 |
| Average impedance | 3 mhm - Ith 20 A 50 Hz for strāvas ķēde |

| | |
|--|--|
| [U _i] rated insulation voltage | Strāvas ķēde 600 V UL 508 Strāvas ķēde 690 V IEC 60947-4-1 Signalling circuit 690 V IEC 60947-4-1 Signalling circuit 690 V IEC 60947-5-1 Signalling circuit 600 V UL 508 Strāvas ķēde 600 V CSA C22.2 No 14 Signalling circuit 600 V CSA C22.2 No 14 |
| Electrical durability | 1,3 M cikli 9 A AC-3 <= 440 V 1,3 M cikli 9 A AC-3e <= 440 V 0,16 M cikli 6 A AC-1 <= 690 V 0,16 M cikli 20 A AC-1 <= 690 V 0,02 M cikli 54 A AC-4 <= 440 V |
| Blokēšanas mehānisma tips | Mechanical |
| Montāžas stiprinājums | Rail Plāksne |
| Standarti | EN/IEC 60947-4-1 GB/T 14048.4 UL 60947-4-1 CSA C22.2 No 60947-4-1 JIS C8201-4-1 |
| Produkta sertifikācija | CB Scheme[RETURN]CCC[RETURN]UL[RETURN]CSA[RETURN]EAC |
| Connections - terminals | Screw clamp terminals 1 1,5...4 mm ² ciets Screw clamp terminals 1 0,75...4 mm ² elastīgs without cable end Screw clamp terminals 1 0,34...2,5 mm ² elastīgs with cable end Screw clamp terminals 2 1,5...4 mm ² ciets Screw clamp terminals 2 0,75...4 mm ² elastīgs without cable end Screw clamp terminals 2 0,34...1,5 mm ² elastīgs with cable end |
| Tightening torque | 0,8...1,3 N.M screw clamp terminals Philips No 2 0,8...1,3 N.M screw clamp terminals flat Ø 6 mm 0,8...1,3 N.m screw clamp terminals pozidriv No 2 |
| Operating time | 10...20 ms coil energisation and NO closing 10...20 ms coil de-energisation and NO opening |
| Safety reliability level | B10d = 1369863 cikli contactor with nominal load EN/ISO 13849-1 B10d = 20000000 cikli contactor with mechanical load EN/ISO 13849-1 |
| Mehāniskā izturība | 5 M cikli |
| Maximum operating rate | 3600 cikls/h |

Papildinošs

| | |
|---------------------------------|---|
| Control circuit voltage limits | Operational: 0.8...1.15 U _c (at <50 °C) Drop-out: 0.2...0.75 U _c (at <50 °C) |
| Inrush power in VA | 30 VA (at 20 °C) |
| Hold-in power consumption in VA | 4,5 VA (at 20 °C) |
| Heat dissipation | 1,3 W |
| Auxiliary contacts type | Instantaneous 1 NO |
| Signalling circuit frequency | <= 400 Hz |
| Minimum switching current | 5 mA for signalling circuit |
| Minimum switching voltage | 17 V for signalling circuit |
| Non overlap distance | 0,5 mm |
| Insulation resistance | > 10 MOhm for signalling circuit |

Vide

| | |
|--|------------------------------|
| IP degree of protection | IP20 VDE 0106 |
| Protective treatment | TC IEC 60068 TC DIN 50016 |
| Apkārtējā gaisa temperatūra darbībai | -25...50 °C |
| Apkārtējā gaisa temperatūra uzglabāšanai | -50...80 °C |
| Operating altitude | 2000 m without derating |

| | |
|-----------------------|---|
| Flame retardance | V1 UL 94 Requirement 2 NF F 16-101 Requirement 2 NF F 16-102 |
| Mechanical robustness | Shocks contactor closed, on X axis10 Gn for 11 ms IEC 60068-2-27 Shocks contactor closed, on Y axis15 Gn for 11 ms IEC 60068-2-27 Shocks contactor closed, on Z axis15 Gn for 11 ms IEC 60068-2-27 Shocks contactor opened, on X axis6 Gn for 11 ms IEC 60068-2-27 Shocks contactor opened, on Y axis10 Gn for 11 ms IEC 60068-2-27 Shocks contactor opened, on Z axis10 Gn for 11 ms IEC 60068-2-27 Vibrations contactor closed4 Gn, 5...300 Hz IEC 60068-2-6 Vibrations contactor opened2 Gn, 5...300 Hz IEC 60068-2-6 |
| Augstums | 58 mm |
| Platums | 90 mm |
| Dziļums | 57 mm |
| Neto svars | 0,39 kg |

Iepakojšanas vienības

| | |
|--------------------------------|-----------|
| Pirmā iepakojuma vienības tips | PCE |
| Vienību skaits 1. iepakojumā | 1 |
| 1. iepakojuma augstums | 6,500 cm |
| 1. iepakojuma platums | 9,000 cm |
| 1. iepakojuma garums | 6,000 cm |
| 1. iepakojuma svars | 368,000 g |
| Otrā iepakojuma vienības tips | S02 |
| Vienību skaits 2. iepakojumā | 25 |
| 2. iepakojuma augstums | 15,000 cm |
| 2. iepakojuma platums | 30,000 cm |
| 2. iepakojuma garums | 40,000 cm |
| 2. iepakojuma svars | 9,415 kg |

Piedāvājiēt ilgtspēju

| | |
|----------------------------------|--|
| Ilgtspējīgs piedāvājuma statuss | Green Premium izstrādājums |
| REACH regula | REACH Deklarācija |
| Nesatur REACH SVHC | Jā |
| ES RoHS direktīva | Atbilstīgs ES RoHS Deklarācija |
| Nesatur toksiskus smagos metālus | Jā |
| Nesatur dzīvsudrabu | Jā |
| Ķīnas RoHS regula | Ķīnas RoHS Deklarācija |
| Informācija par RoHS izņēmumiem | Jā |
| Vides informācijas publicēšana | Produkta Ietekme Uz Vidi |
| Cirkularitātes profils | Informācija Par Eksploatācijas Izbeigšanu |
| WEEE | Eiropas Savienības tirgū no šī produkta ir jāatbrīvojas, ievērojot noteiktu atkritumu savākšanas kārtību, un produkts nedrīkst nonākt sadzīves atkritumu tvertnēs. |

Līguma garantija

| | |
|-----------|-----------|
| Garantija | 18 months |
|-----------|-----------|