



Galvenā

Valve product range	Venta
Produkta vai sastāvdaļas veids	Valve
Valve type	Globe
Valve product series	V231
Valve model	V231/32/16
Medium compatibility	Steam Water Glycol 25 % Glycol 30 % Glycol 50 %
Valve configuration	2-Way
Valve connection type	Flanged
Valve connection size	DN32 (ISO 7005-2)
Pipe size	32 mm
Body size	32 mm (1-1/4 in)
Flow characteristic	Equal percentage
Flow coefficient	18.5 cv 16 kvs
Pressure class	PN25
Operating fluid temperature	-20...150 °C
Pressure fluid max delta P normal life	799,79 kPa
Saturated steam temperature	-20...150 °C
Control valve rangeability	Greater than 200:1
Stroke length	20 mm
Seat leakage	Port A: Less than 0.02 % of kvs
Stem flow action	Stem up closed
Trim material	Stainless steel
Body material	Nodular cast iron EN-JS 1025
Seat material	Port A: stainless steel AISI 303
Stem material	Stainless steel AISI 303
Plug material	Stainless steel AISI 303
Stem seal material	EPDM (ethylene propylene diene monomer)
Seating seal material	Port A: metal to metal
Packing material	EPDM (ethylene propylene diene monomer)
Targeted region	Europe Asia Pacific. Australia.

Iepakojšanas vienības

Pirmā iepakojuma vienības tips	PCE
Vienību skaits 1. iepakojumā	1
1. iepakojuma augstums	14,0 cm
1. iepakojuma platums	18,5 cm
1. iepakojuma garums	26,5 cm
1. iepakojuma svars	7,65 kg

Piedāvājiem ilgtspēju

ES RoHS direktīva	Nav piemērojams, uz to neattiecas ES RoHS juridiskās saistības
Ķīnas RoHS regula	Ķīnas RoHS Deklarācija
Vides informācijas publiskošana	Produkta Ietekme Uz Vidi
Cirkularitātes profils	Nav jāveic īpašas darbības, lai nodotu otrreizējai pārstrādei