



### Galvenā

Valve product range	Venta
Produkta vai sastāvdaļas veids	Valve
Valve type	Globe
Valve product series	V231
Valve model	V231/50/38
Medium compatibility	Steam Water Glycol 25 % Glycol 30 % Glycol 50 %
Valve configuration	2-Way
Valve connection type	Flanged
Valve connection size	DN50 (ISO 7005-2)
Pipe size	50 mm
Body size	50 mm (2 in)
Flow characteristic	Equal percentage
Flow coefficient	43.94 cv 38 kvs
Pressure class	PN25
Operating fluid temperature	-20...150 °C
Pressure fluid max delta P normal life	799,79 kPa
Saturated steam temperature	-20...150 °C
Control valve rangeability	Greater than 200:1
Stroke length	20 mm
Seat leakage	Port A: Less than 0.02 % of kvs
Stem flow action	Stem up closed
Trim material	Stainless steel
Body material	Nodular cast iron EN-JS 1025
Seat material	Port A: stainless steel AISI 303
Stem material	Stainless steel AISI 303
Plug material	Stainless steel AISI 303
Stem seal material	EPDM (ethylene propylene diene monomer)
Seating seal material	Port A: metal to metal
Packing material	EPDM (ethylene propylene diene monomer)
Targeted region	Europe Asia Pacific. Australia.

### Iepakojšanas vienības

Pirmā iepakojuma vienības tips	PCE
Vienību skaits 1. iepakojumā	1
1. iepakojuma augstums	16,5 cm
1. iepakojuma platums	23,5 cm
1. iepakojuma garums	29,5 cm
1. iepakojuma svars	12,45 kg

## Piedāvājiem ilgtspēju

ES RoHS direktīva	Nav piemērojams, uz to neattiecas ES RoHS juridiskās saistības
Ķīnas RoHS regula	<a href="#">Ķīnas RoHS Deklarācija</a>
Vides informācijas publiskošana	<a href="#">Produkta Ietekme Uz Vidi</a>
Cirkularitātes profils	Nav jāveic īpašas darbības, lai nodotu otrreizējai pārstrādei