



Galvenā

Produkta sērija	Altivar
Produkta vai sastāvdaļas veids	Communication module
Aksesuāru / rezerves daļu kategorija	Communication accessories

Papildinošs

Produktu saderība	Lexium 32M
Range compatibility	Altivar Machine ATV320 Altivar 32 Lexium 32
Komunikācijas porta protokols	Modbus TCP Ethernet/IP
Electrical connection	1 connector RJ45, Ethernet/IP 1 connector RJ45, Modbus TCP
Pārraides ātrums	10/100 Mbps
Addressing	IP addressing manual, BOOTP or DHCP
Apmaiņas režīms	Half duplex and full duplex
Communication service	Up to 8 connections (includes connections of Modbus TCP/Ethernet IP) Ethernet IP/Modbus TCP FDR Agent Ethernet IP/Modbus TCP Read holding registers (03), 63 words max Modbus TCP Read input registers (04), 63 words max Modbus TCP Write single register (06) Modbus TCP Write multiple registers (16), 63 words max Modbus TCP Read/Write multiple registers (23) Modbus TCP Read device identification (43) Modbus TCP Diagnostics (08) Modbus TCP I/O scanner : read/write, 6 words maximum Modbus TCP Communication monitoring Modbus TCP SNMP agent Ethernet IP Master/Slave hierarchy ODVA AC drive profile and CiA 402 profile Ethernet IP Fixed communication monitoring adjusted by Ethernet IP scanner adaptor (Master) Ethernet IP
Display type	1 LED MS (Module Status) 1 LED NS (Network Status) 1 LED Ethernet port activity 1 LED Modbus TCP port activity
Neto svars	0,3 kg

The information provided in this documentation contains general descriptions and/or technical characteristics of the performance of the products contained herein. This documentation is not intended as a substitute for and is not to be used for determining suitability or reliability of these products for specific user applications. It is the duty of any such user or integrator to perform the appropriate and complete risk analysis, evaluation and testing of the products with respect to the relevant specific application or use thereof. Neither Schneider Electric Industries SAS nor any of its affiliates or subsidiaries shall be responsible or liable for misuse of the information contained herein.

Iepakojšanas vienības

Pirmā iepakojuma vienības tips	PCE
Vienību skaits 1. iepakojumā	1
1. iepakojuma augstums	4,200 cm
1. iepakojuma platums	6,100 cm
1. iepakojuma garums	9,000 cm
1. iepakojuma svars	60,000 g
Otrā iepakojuma vienības tips	S03
Vienību skaits 2. iepakojumā	100
2. iepakojuma augstums	30,000 cm
2. iepakojuma platums	30,000 cm
2. iepakojuma garums	40,000 cm
2. iepakojuma svars	6,590 kg

Piedāvājiēt ilgtspēju

Ilgtspējīgs piedāvājuma statuss	Green Premium izstrādājums
REACH regula	REACH Deklarācija
ES RoHS direktīva	Proaktīva atbilstība (uz izstrādājumu neattiecas ES RoHS juridiskās saistības) ES RoHS deklarācija
Nesatur toksiskus smagos metālus	Jā
Nesatur dzīvsudrabu	Jā
Ķīnas RoHS regula	Ķīnas RoHS Deklarācija
Informācija par RoHS izņēmumiem	Jā
Vides informācijas publicēšana	Produkta Ietekme Uz Vidi
Cirkularitātes profils	Nav jāveic īpašas darbības, lai nodotu otrreizējai pārstrādei
Nesatur PVH	Jā

Līguma garantija

Garantija	18 months
-----------	-----------