



## Galvenā

Diapazons	TeSys
Produkta nosaukums	TeSys VARIO
Ierīces īsais nosaukums	VCF
Produkta vai sastāvdaļas veids	Enclosed emergency stop switch disconnecter
Performance level	High performance
Polu skaits	3P
Vadības veids	Rotary handle
Handle colour	Red
Handle front plate colour	Yellow
Rotary handle padlocking	1 to 3 padlocks 4...8 mm

## Papildinošs

Markējums	0 - 1
[Ue] rated operational voltage	690 V AC
[Uimp] rated impulse withstand voltage	8 kV
[Ithe] conventional enclosed thermal current	10 A
[Ie] rated operational current	8,1 A AC-23A)400 V
Rated operational power in W	4 kW 400 V AC-23) 3 kW 400 V AC-3)
Intermittent duty class	30
Making capacity ( I rms)	120 A 400 V AC-21A 120 A 400 V AC-22A 120 A 400 V AC-23A
[Icm] rated short-circuit making capacity	1 kA 400 V at Ipeak
[Icw] rated short-time withstand Rms current	300 A 400 V 1 s
Rated conditional short-circuit current	10 kA 400 V 12 A aM 10 kA 400 V 12 A gG
Breaking capacity	120 A 400 V AC-21A) 120 A 400 V AC-22A) 120 A 400 V AC-23A)
Mehāniskā izturība	100000 cikli
Electrical durability	100000 Cikli AC-21 30000 cikli DC-1...5
Vides raksturlielumi	Standard environment
Suitability for isolation	Yes
Connections - terminals	Strāvas ķēde screw clamp terminals 2,5...4 mm <sup>2</sup> elastīgs - with cable end Protective earth screw clamp terminals 2,5...4 mm <sup>2</sup> elastīgs - with cable end Shield cable earth cable clips
Tightening torque	2,1 N.m screw clamp terminals
Fire resistance	960 °C IEC 60595-2-1
Handle front plate dimension	60 x 60 mm
Augstums	146 mm
Platums	90 mm
Dziļums	131 mm
Neto svars	0,5 kg

The information provided in this documentation contains general descriptions and/or technical characteristics of the performance of the products contained herein. This documentation is not intended as a substitute for and is not to be used for determining suitability or reliability of these products for specific user applications. It is the duty of any such user or integrator to perform the appropriate and complete risk analysis, evaluation and testing of the products with respect to the relevant specific application or use thereof. Neither Schneider Electric Industries SAS nor any of its affiliates or subsidiaries shall be responsible or liable for misuse of the information contained herein.

## Vide

Standarti	IEC 60947-4-1 IEC 60204
Protective treatment	TC
IP aizsardzības pakāpe	IP65 atbilst IEC&nbsp;60529
Mechanical robustness	Vibrations 10...150 Hz 1 gn) IEC 60068-2-6 Shocks 11 ms 30 Gn) IEC 60068-2-27
Apkārtējā gaisa temperatūra darbībai	-20...50 °C

## Iepakojšanas vienības

Pirmā iepakojuma vienības tips	PCE
Vienību skaits 1. iepakojumā	1
1. iepakojuma augstums	14,5 cm
1. iepakojuma platums	11,6 cm
1. iepakojuma garums	16,0 cm
1. iepakojuma svars	470,0 g

## Piedāvājiem ilgtspēju

Ilgtspējīgs piedāvājuma statuss	Green Premium izstrādājums
REACH regula	<a href="#">REACH Deklarācija</a>
ES RoHS direktīva	Atbilst izņēmumiem
Nesatur toksiskus smagos metālus	Jā
Nesatur dzīvsudrabu	Jā
Ķīnas RoHS regula	<a href="#">Ķīnas RoHS Deklarācija</a>
Informācija par RoHS izņēmumiem	<a href="#">Jā</a>
Vides informācijas publiskošana	<a href="#">Produkta Ietekme Uz Vidi</a>
Cirkularitātes profils	Nav jāveic īpašas darbības, lai nodotu atbilstīgai pārstrādei

## Līguma garantija

Garantija	18 months
-----------	-----------