

# Product datasheet

Specifications



## Fiber filter for Side Connected Cooling Unit, Climasys CU, 3 - 3,2 - 4kW

NSYCUACC004DG

EAN Code: 3606486379271

### Main

Range	ClimaSys
Product name	ClimaSys CU
Product or component type	Filter
Range compatibility	ClimaSys Climasys CU cooling unit
Accessory / separate part category	Thermal management accessory

### Complementary

Type of ventilation filter	G3 EN 779
Mounting location	Side
Product destination	For side-mounting cooling unit - power: 3200 W For side-mounting cooling unit - power: 4000 W
Accessory / separate part destination	ClimaSys cooling unit
Quantity per set	Set of 5
Material	Polyolefin
Net weight	0.04 kg
Width	470 mm
Height	380 mm
Thickness	5 mm

### Environment

Flame retardance	K1/F1 conforming to DIN 53 438
------------------	--------------------------------

### Packing Units

Unit Type of Package 1	PCE
Number of Units in Package 1	1
Package 1 Height	1.000 cm
Package 1 Width	40.000 cm
Package 1 Length	50.000 cm
Package 1 Weight	80.000 g
Unit Type of Package 2	CAR
Number of Units in Package 2	5
Package 2 Height	5.000 cm

Disclaimer: This documentation is not intended as a substitute for and is not to be used for determining suitability or reliability of these products for specific user applications

Package 2 Width	40.000 cm
Package 2 Length	50.000 cm
Package 2 Weight	400.000 g
Unit Type of Package 3	PAL
Number of Units in Package 3	50
Package 3 Height	29.000 cm
Package 3 Width	45.000 cm
Package 3 Length	120.000 cm
Package 3 Weight	4.000 kg

## Contractual warranty


Warranty	18 months
----------	-----------

# Environmental Data


Schneider Electric aims to achieve Net Zero status by 2050 through supply chain partnerships, lower impact materials, and circularity via our ongoing “Use Better, Use Longer, Use Again” campaign to extend product lifetimes and recyclability.

[How this information helps you](#) >

## Use Better


 <b>Materials and Substances</b>	
Packaging made with recycled cardboard	No
Packaging without single use plastic	No
<a href="#">EU RoHS Directive</a>	Pro-active compliance (Product out of EU RoHS legal scope)
REACH Regulation	<a href="#">REACH Declaration</a>
China RoHS Regulation	<a href="#">China RoHS declaration</a>

## Use Again

 <b>Repack and remanufacture</b>	
Take-back	No

Technical Illustration

Wiring diagram



Offer Marketing Illustration

Product benefits / Features

---

The infographic features a central image of three Schneider Electric NSYCUACC004DG cooling units in different sizes. Surrounding this central image are six circular icons, each with a corresponding text description of a product benefit or feature.

- Connected with alarming and setting data**: Represented by an icon of a speaker with sound waves.
- Easy selection with 40 references IEC & UL**: Represented by an icon of a 2x2 grid with checkmarks.
- 3 redundant modes for critical application**: Represented by an icon of a server rack with three arrows pointing to different sections.
- Recycled packaging, good energy efficiency ratio**: Represented by an icon of a recycling symbol with a leaf.
- 30% Smaller and lighter Cooling Units**: Represented by an icon of a square with a diagonal line and a smaller square.
- Easy mounting with 3 positions, easy spare parts replacement**: Represented by an icon of a clock with a checkmark.

Image of product / Alternate images

Alternative

---

