

Conventional Thermal Detector ED5351E

Instruction Sheet
R10069GB1



Schneider Electric
www.se.com/buildings

R10069GB1
March 2024

© 2018-2024 – Schneider Electric. All Rights Reserved. This information is only to be used as guidance. Subject to changes and errors.

Contents

Safety Information	4
1 Conventional Thermal Detector ED5351E	4
1.1 Conventional 300 series detectors with intelligent features.....	4
1.2 Test and Maintenance.....	5
1.2.1 S300RTU test unit	5
1.3 Product Codes	5

Safety Information

Electrical equipment should be installed, operated, serviced, and maintained only by qualified personnel. No responsibility is assumed by Schneider Electric for any consequences arising out of the use of this material.

A qualified person is one who has skills and knowledge related to the construction, installation, and operation of electrical equipment and has received safety training to recognize and avoid the hazards involved.

1 Conventional Thermal Detector ED5351E

The ED5351E (FFS06714650E) thermal detector is a rate-of-rise and fixed temperature detector with a nominal alarm temperature of 58°C. It is tested and certified to comply with the EN54 part 5 standard, class A1R.

Thermal detectors are used in environments where smoke detection is not suitable.

1.1 Conventional 300 series detectors with intelligent features

The 300 series of fire detectors from Esmi have innovative features and functionality that earlier were seen only in intelligent addressable systems.

Thermal detectors are available for class A1R, A2S as well as for the high temperature class BS.

The 300 series of detectors are compact and have an attractive low profile design.

A hand-held test and maintenance tool unit provides for advanced maintenance features.

Note!

- It is recommended not to cover or paint the detectors.
- Detectors have to be installed according to separate installation instructions. Function of detector must be tested at regular intervals.
- Recommended cleaning procedure of smoke detectors is described in documentation accompanying the detectors.
- Concerning information of compatible bases please refer to the datasheets of the B400 series of bases.

1.2 Test and Maintenance

1.2.1 S300RTU test unit

The S300RTU is a low cost test device for activation of alarm condition. The unit has a coded laser beam, which activates an alarm condition in the detector at distances of up to 5m from the detector. It is an ideal tool for initial commissioning and routine testing.

1.3 Product Codes

Product	Product code
ED5351E Thermal Detector	FFS06714650E
S300RTU	FFS06718700