

# GT 60-40-25



## Specifications

|                       |             |
|-----------------------|-------------|
| ETI Code              | 001102121   |
| Description           | GT 60-40-25 |
| Class name            | Enclosure   |
| Height (mm)           | 600         |
| Width (mm)            | 400         |
| Depth (mm)            | 250         |
| IP rating             | IP66        |
| Color                 | RAL 7035    |
| Application           | Indoor use  |
| Mechanical resistance | IK10        |
| Protection Class      | I           |

[Online product page](#) 

## Other documentation



[Technical data catalogue](#)  
[3D Model](#)  
[Instruction manual](#)  
[CE declaration](#)  
[Eplan file](#)  
[BIM File](#)

## ETIM international clasification

|                                      |                           |
|--------------------------------------|---------------------------|
| Classification                       | EC000058                  |
| Class name                           | Empty cabinet             |
| Mounting method                      | Surface mounted (plaster) |
| Type of door                         | Single                    |
| Transparent cover/door               |                           |
| With lock                            | 1                         |
| Height                               | 600mm                     |
| Width                                | 400mm                     |
| Depth                                | 250mm                     |
| Built-in depth                       | 250mm                     |
| Colour                               | Grey                      |
| RAL-number                           | 7035                      |
| Number of openings for flange plates | 1                         |
| Housing material                     | Steel                     |
| Surface protection                   | Powder coating            |
| With mounting plate                  | 1                         |
| Suitable for outdoor use             |                           |
| Degree of protection (IP)            | IP66                      |
| Protection class                     | I                         |
| Impact strength                      | IK10                      |