




---

 PRODUCT-DETAILS

# UAF95-30-00RA-72

## UAF95-30RA 20-60V DC Contactor




---

**General Information**

Extended Product Type	UAF95-30-00RA-72
Product ID	1SFL437024R7200
EAN	7320500355183
Catalog Description	UAF95-30RA 20-60V DC Contactor
Long Description	A 3-phase Contactor suitable for Capacitor switching application. Maximum permissible peak current 100 times the nominal RMS current. Operated with a control voltage 20-60 V, AC/DC

---

**Ordering**

Minimum Order Quantity	1 piece
Customs Tariff Number	85364900

---

**Popular Downloads**

Data Sheet, Technical Information	1SBC101145L0202
Instructions and	5309660-60

Manuals

**Dimensions**

Product Net Width	90 mm
Product Net Depth / Length	155.6 mm
Product Net Height	170 mm
Product Net Weight	1.8 kg

**Technical**

Number of Main Contacts NO	3
Number of Main Contacts NC	0
Number of Auxiliary Contacts NO	0
Number of Auxiliary Contacts NC	0
Number of Poles	3P
Rated Operational Voltage	Main Circuit 1000 V
Conventional Free-air Thermal Current (I <sub>th</sub> )	acc. to IEC 60947-4-1, Open Contactors $\Theta = 40\text{ }^{\circ}\text{C}$ 145 A
Rated Operational Current AC-1 (I <sub>e</sub> )	(690 V) 40 °C 145 A (690 V) 55 °C 135 A (690 V) 70 °C 115 A
Rated Operational Current AC-3 (I <sub>e</sub> )	(415 V) 55 °C 96 A (440 V) 55 °C 93 A (500 V) 55 °C 80 A (690 V) 55 °C 65 A (1000 V) 55 °C 30 A (380 / 400 V) 55 °C 96 A (220 / 230 / 240 V) 55 °C 96
Rated Operational Power AC-3 (P <sub>e</sub> )	(380 / 400 V) 45 kW
Rated Operational Power AC-6b (P <sub>e</sub> )	(230 / 240 V) 40 °C, 50 / 60 Hz 35 kvar (230 / 240 V) 55 °C, 50 / 60 Hz 35 kvar (230 / 240 V) 70 °C, 50 / 60 Hz 30 kvar (400 / 415 V) 40 °C, 50 / 60 Hz 65 kvar (400 / 415 V) 70 °C, 50 / 60 Hz 55 kvar (400 / 415 V) 55 °C, 50 / 60 Hz 65 kvar (440 V) 40 °C, 50 / 60 Hz 65 kvar (440 V) 55 °C, 50 / 60 Hz 65 kvar (440 V) 70 °C, 50 / 60 Hz 55 kvar (500 / 550 V), 40 °C, 50 / 60 Hz 70 kvar (500 / 550 V) 55 °C, 50 / 60 Hz 70 kvar (500 / 550 V) 70 °C, 50 / 60 Hz 60 kvar (690 V) 40 °C, 50 / 60 Hz 80 kvar (690 V) 55 °C, 50 / 60 Hz 80 kvar (690 V) 70 °C, 50 / 60 Hz 70 kvar
Rated Breaking Capacity AC-3	8 x I <sub>e</sub> AC-3
Rated Making Capacity AC-3	10 x I <sub>e</sub> AC-3
Maximum Breaking Capacity	cos phi=0.45 (cos phi=0.35 for I <sub>e</sub> > 100 A) at 440 V 1160 A cos phi=0.45 (cos phi=0.35 for I <sub>e</sub> > 100 A) at 690 V 800 A
Rated Insulation Voltage (U <sub>i</sub> )	acc. to IEC 60947-4-1 and VDE 0110 (Gr. C) 1000 V acc. to UL/CSA 600 V
Rated Impulse Withstand Voltage (U <sub>imp</sub> )	Main Circuit 8 kV

)	
Maximum Electrical Switching Frequency	(AC-1) 300 cycles per hour (AC-2 / AC-4) 150 cycles per hour (AC-3) 300 cycles per hour
Mechanical Durability	10 million
Maximum Mechanical Switching Frequency	300 cycles per hour
Coil Operating Limits	(acc. to IEC 60947-4-1) 0.85 x U <sub>c</sub> Min. ... 1.1 x U <sub>c</sub> Max. (at θ ≤ 70 °C)
Rated Control Circuit Voltage (U <sub>c</sub> )	DC Operation 20 ... 60 V
Coil Consumption	Holding at Max. Rated Control Circuit Voltage 50 Hz 7 V·A Holding at Max. Rated Control Circuit Voltage 60 Hz 7 V·A Holding at Max. Rated Control Circuit Voltage DC 2 W Pull-in at Max. Rated Control Circuit Voltage 50 Hz 350 V·A Pull-in at Max. Rated Control Circuit Voltage 60 Hz 350 V·A Pull-in at Max. Rated Control Circuit Voltage DC 400 V·A
Power Loss	at Rated Operating Conditions per Pole 3.5 W
Operate Time	Between Coil De-energization and NC Contact Closing 60 ... 130 ms Between Coil De-energization and NO Contact Opening 55 ... 125 ms Between Coil Energization and NC Contact Opening 27 ... 77 ms Between Coil Energization and NO Contact Closing 30 ... 80 ms
Connecting Capacity Main Circuit	Bar 30 mm <sup>2</sup> Flexible with Cable End 1 x 10 ... 70 mm <sup>2</sup> Rigid 2 x 6 ... 65 mm <sup>2</sup>
Connecting Capacity Auxiliary Circuit	Flexible with Ferrule 2x 0.75 ... 2.5 mm <sup>2</sup> Flexible with Insulated Ferrule 2x 0.75 ... 2.5 mm <sup>2</sup> Flexible 2x0.75 ... 2.5 mm <sup>2</sup> Solid 1 x 1 ... 4 mm <sup>2</sup> Stranded 2 x 1 ... 4 mm <sup>2</sup>
Connecting Capacity	Bar 30 mm <sup>2</sup> Flexible with Cable End 2 x 6 ... 35 mm <sup>2</sup> Rigid 2 x 6 ... 65 mm <sup>2</sup>
Degree of Protection	acc. to IEC 60529, IEC 60947-1, EN 60529 Coil Terminals IP20 acc. to IEC 60529, IEC 60947-1, EN 60529 Main Terminals IP10
Connecting Terminals (delivered in open position) Main Poles	M8 hexagon socket screw with single connector
Tightening Torque	Main Circuit 8 N·m
Terminal Type	Cable Clamp
Product Name	Block Contactor

**Technical UL/CSA**

Maximum Operating Voltage UL/CSA	Main Circuit 600 V
Horsepower Rating UL/CSA	(200 V AC) Three Phase 30 hp (208 V AC) Three Phase 30 hp (220 ... 240 V AC) Three Phase 30 hp (440 ... 480 V AC) Three Phase 60 hp (550 ... 600 V AC) Three Phase 75 hp

**Environmental**

Ambient Air Temperature	Close to Contactor Fitted with Thermal O/L Relay (0.85 ... 1.1 U <sub>c</sub> ) -25 ... 50 °C Close to Contactor without Thermal O/L Relay (0.85 ... 1.1 U <sub>c</sub> ) -40 ... 70 °C Close to Contactor for Storage -60 ... +80 °C
Maximum Operating Altitude Permissible	Without Derating 3000 m
Resistance to Shock acc. to IEC 60068-2-27	Half-sine Pulse for 11 ms, No Change in Contact Position, Open, Shock Direction: A 20 g

Half-sine Pulse for 11 ms, No Change in Contact Position, Closed, Shock  
 Direction: A 20 g  
 Half-sine Pulse for 11 ms, No Change in Contact Position, Closed, Shock  
 Direction: B1 15 g  
 Half-sine Pulse for 11 ms, No Change in Contact Position, Closed, Shock  
 Direction: C1 20 g  
 Half-sine Pulse for 11 ms, No Change in Contact Position, Closed, Shock  
 Direction: C2 20 g  
 Half-sine Pulse for 11 ms, No Change in Contact Position, Open, Shock  
 Direction: B1 5 g  
 Half-sine Pulse for 11 ms, No Change in Contact Position, Open, Shock  
 Direction: B2 15 g  
 Half-sine Pulse for 11 ms, No Change in Contact Position, Open, Shock  
 Direction: C1 20 g  
 Half-sine Pulse for 11 ms, No Change in Contact Position, Open, Shock  
 Direction: C2 20 g

**Material Compliance**

Conflict Minerals Reporting Template (CMRT)	9AKK108467A5658
REACH Declaration	2CMT2021-006202
RoHS Information	2CMT2021-006277
RoHS Status	Following EU Directive 2011/65/EU and Amendment 2015/863 July 22, 2019
Toxic Substances Control Act - TSCA	2CMT2023-006525
WEEE B2C / B2B	Business To Business
WEEE Category	5. Small Equipment (No External Dimension More Than 50 cm)

**Certificates and Declarations**

CB Certificate	CB_CN64637
cULus Certificate	20160916- E36588
Declaration of Conformity - CE	9AKK108471A1807
Declaration of Conformity - UKCA	2CMT2020-006118

**Container Information**

Package Level 1 Units	box 1 piece
Package Level 1 Width	170 mm
Package Level 1 Depth / Length	140 mm
Package Level 1 Height	170 mm
Package Level 1 Gross Weight	2 kg
Package Level 1 EAN	7320500355183

**External Classifications and Standards**

Object Classification Code	Q
ETIM 7	EC001079 - Capacitor contactor
ETIM 8	EC001079 - Capacitor contactor
ETIM 9	EC001079 - Capacitor contactor
eClass	V11.0 : 27371006

UNSPSC

39121529

IDEA Granular Category  
Code (IGCC)

4756 >> Capacitor magnet contactor

---

---

## Categories

---

Low Voltage Products and Systems → Control Products → Contactors → Block Contactors → UA and UA..RA Contactors → UA95RA

