



The cable may be used for installation in fixed installed conduit- or duct systems, and also as connecting cable in cupboards and armatures.

STANDARDS

Product EN 50525-3-31

DESCRIPTION

H07Z1-R (FQ Easy™) is a halogen free, HFFR-insulated house wiring cable with one circular, stranded copper conductor. The cable is designed according to HD 21.3 in applicable parts. The conductor has resistance and number of wires according to IEC 60228 class 2. The insulation is marked "NEXANS GS SEMKO Ds2d2a2". H07Z1-R (FQ Easy™) meets the requirements for fire classification Dcas2d2a2 according to CPR. The conductor insulation shall be protected against UV light that can occur for example in light fixtures and light signs. The cable is certified by Intertek SEMKO.

Certification

Certified by Intertek SEMKO.

Quality and environmental management system

Certified according to ISO 9001, ISO/TS 16949 and ISO 14001.



Conductor flexibility
Stranded class 2



Halogen free
Yes



Rated Voltage Uo/U
(Um)
450/750 V



Minimum
installation
temperature
0 °C



Maximum operating
temperature
70 °C



Bending factor
when laying
8 (xD)



Smoke density
IEC 61034



Gases corrosivity
IEC 60754-2

CHARACTERISTICS

Construction characteristics

| | |
|-----------------------|-----------------------|
| Conductor material | Copper |
| Conductor shape | Circular |
| Conductor flexibility | Stranded class 2 |
| Insulation | Halogen free compound |
| Halogen free | Yes |

Dimensional characteristics

| | |
|-----------------|---|
| Number of cores | 1 |
|-----------------|---|

Electrical characteristics

| | |
|-------------------------|-----------|
| Rated Voltage Uo/U (Um) | 450/750 V |
|-------------------------|-----------|

Usage characteristics

| | |
|----------------------------------|-------------|
| Minimum installation temperature | 0 °C |
| Maximum operating temperature | 70 °C |
| Bending factor when laying | 8 (xD) |
| Smoke density | IEC 61034 |
| Gases corrosivity | IEC 60754-2 |

PRODUCT LIST

| Nexans Ref. | Country Ref. | Name | Colour | Conductor cross-section [mm ²] | Nominal outer diameter [mm] |
|---------------------|--------------|---|----------------|--|-----------------------------|
| ■ 11485340-207-02 - | | H07Z1-R 450/750 V 1,5 | Grey | 1,5 | 3,0 |
| ■ 11485340-410-02 - | | H07Z1-R 450/750 V 1,5 | Orange | 1,5 | 3,0 |
| ■ 11485340-232-02 - | | H07Z1-R 450/750 V 1,5 | Yellow / green | 1,5 | 3,0 |
| ■ 11485340-411-02 - | | H07Z1-R 450/750 V 1,5 | Black | 1,5 | 3,0 |
| ■ 11485340-412-02 - | | H07Z1-R 450/750 V 1,5 | White | 1,5 | 3,0 |
| ■ 11485340-208-02 - | | H07Z1-R 450/750 V 1,5 | Brown | 1,5 | 3,0 |
| ■ 11485340-204-02 - | | H07Z1-R 450/750 V 1,5 | Blue | 1,5 | 3,0 |
| ■ 11485440-208-02 - | | H07Z1-R 450/750 V 2,5 | Brown | 2,5 | 3,6 |
| ■ 11485440-412-02 - | | H07Z1-R 450/750 V 2,5 | White | 2,5 | 3,6 |
| ■ 11485440-411-02 - | | H07Z1-R 450/750 V 2,5 | Black | 2,5 | 3,6 |
| ■ 11485440-204-02 - | | H07Z1-R 450/750 V 2,5 | Blue | 2,5 | 3,6 |
| ■ 11485440-232-02 - | | H07Z1-R 450/750 V 2,5 | Yellow / green | 2,5 | 3,6 |
| ■ 11485440-207-02 - | | H07Z1-R 450/750 V 2,5 | Grey | 2,5 | 3,6 |
| ■ 11485440-410-02 - | | H07Z1-R 450/750 V 2,5 | Orange | 2,5 | 3,6 |
| ■ 11485340-203-02 - | | H07Z1-R 450/750 V 1,5 | Red | 1,5 | 3,0 |
| ■ 11485340-211-02 - | | FQ Easy™ 1,5 mm ² 450/750 V Violett | Violet | 1,5 | 3,0 |

■ = Make to order, ■ = In stock,

SELLING AND DELIVERY INFORMATION

FQ Easy™ H07Z1-R is delivered in lengths of 100 m. The drum is marked with manufacturer, type of cable and length.