

Wall mounted socket

Part no. 27004




- screw terminals
- external fixing
- cable entry at top

Technical specifications

Ampere	16 A
Poles	5 p
Voltage	400 V
Clock position	6 h
Hertz	50-60 Hz
Connection technology	Screw terminals
Contact	standard
Protection type	IP44
Weight	270 g
Certifications	VDE

Drawing



Drawing 1 MB 463	Amp. Poles	16			32		
		3	4	5	3	4	5
	a	95	93	92.5	102	102	102
	b	73.5	87.5	87.5	94	94	94
	c	93	107.5	110	115.5	115.5	119.5
	d	55.5	55.5	55.5	62	62	62
	e	61	76	76	84	84	84
	f1	5.3	5.3	5.3	5.1	5.1	5.1
	f2	5.3	5.3	5.3	5.1	5.1	5.1
	h	139	139	136.5	160	160	156.5
	i	19.8	21.5	21.5	26.5	26.5	26.5
	M	M20x M25x M25x	M25x M25x M25x	M25x M25x M25x	M32x M32x M32x	M32x M32x M32x	
		1.5	1.5	1.5	1.5	1.5	1.5
		1.5	1.5	1.5	2.5	2.5	2.5
		—4	—4	—4	—6	—6	—6

Terminal for cond. cross section (mm²) min.-max.