

ETITEC GSMF T123 275/25 1+0



Specifications

ETI Code	002440723
Description	ETITEC GSMF T123 275/25 1+0
Class name	Surge arrester
Function	SPD
Type	T1, T2, T3
limp(10/350) impulse current (kA)	25
Max. discharge current I _{max} , 8/20 (kA)	65
Remote signalisation	FALSE
Network system	TN
Catalogue Group	ETITEC GSMF
In 8/20 (kA)	25
Number of modules	1
Up - Voltage protection level (kV)	1,5
Leakage current	NO
Applied technology	GDT
Built-in depth (mm)	86
AC max continuous operating voltage U _c	275

[Online product page](#)

Other documentation

[Instruction manual](#)[CE declaration](#)

ETIM international clasification

Classification	EC001457
Class name	Combined arrester for power supply systems
System configuration DC	
System configuration IT	
System configuration TN	1
System configuration TN-C	1
System configuration TN-S	1
System configuration TT	
System configuration other	
Number of poles	1
Lightning impulse current (10/350 µs)	25
Max. continuous voltage AC	275
Nominal voltage AC	230
Voltage protection level	1,5
Follow current extinguishing capability	75
Specific energy (W/R)	156,2
Max. conductor cross section solid (solid, stranded)	35
Max. conductor cross section flexible (fine-strand)	25
Mounting method	DIN rail (top hat rail) 35 mm
Construction size	2 modular spacing
Remote signalling	
Signalling at the device	Optical
Test class	Type 1 + 2
Exhausting	
Integrated backup fuse	1
Degree of protection (IP)	IP20