

ETITEC ML T123 300/12,5 3+0



Specifications

ETI Code	002440665
Description	ETITEC ML T123 300/12,5 3+0
Class name	Surge arrester
Function	SPD
Type	T1, T2, T3
limp(10/350) impulse current (kA)	12,5
Max. discharge current I _{max} , 8/20 (kA)	40
Remote signalisation	FALSE
Network system	TN-C
Catalogue Group	ETITEC ML
In 8/20 (kA)	20
Number of modules	3
Up - Voltage protection level (kV)	1,5
Leakage current	YES
Applied technology	MOV
Built-in depth (mm)	70
AC max continous operating voltage U _c	300

[Online product page](#)

Other documentation



[Technical data catalogue](#)
[3D Model](#)
[Instruction manual](#)
[CE declaration](#)
[Eplan file](#)

ETIM international clasification

Classification	EC001457
Class name	Combined arrester for power supply systems
System configuration DC	
System configuration IT	
System configuration TN-C	1
System configuration TN-S	
System configuration TT	
System configuration other	
Number of poles	3
Lightning impulse current (10/350 µs)	12,5
Max. continuous voltage AC	300
Nominal voltage AC	230
Voltage protection level	1,5
Specific energy (W/R)	39
Max. conductor cross section solid (solid, stranded)	35
Max. conductor cross section flexible (fine-strand)	25
Mounting method	DIN rail (top hat rail) 35 mm
Construction size	3 modular spacing
Remote signalling	
Signalling at the device	Optical
Test class	Type 1 + 2
Exhausting	
Integrated backup fuse	
Degree of protection (IP)	IP20