

# LUXA 103 S360-28 KNX DE WH

Item no.: 1039073



## Presence and motion detectors Ceiling installation indoor

### Description

- Presence detector (PIR) for ceiling installation in suspended ceilings indoor
- Rectangular detection area 360°, 28 x 5 m (140 m<sup>2</sup>) at 3 m mounting height
- For KNX bus system, 2 light channels and 2 presence channels for HVAC control
- 2 channels light with 1 light measurement
- Automatic lighting control with constant light control or switching mode
- Dimmable lighting in switching mode with and without daylight influence
- Integrated temperature sensor
- Day / night switching via telegram
- Stand-by functionality (orientation light)
- 3 logic channels (AND/OR/XOR)
- KNX Data-Secure
- Operation as fully or semi-automatic possible
- Manual override possible via external KNX push-buttons
- One directional brightness measurement (mixed light measurement)
- Simple adjustment of the brightness measurement
- Short-term presence
- Selectable control speed
- Teach-in function
- Scene functionality
- Locking functions
- Switch-on delay and presence follow-up time adjustable
- Extension of the detection area through parallel connection
- Detection sensitivity can be changed for outdoor use
- Test mode for checking function and detection area
- Setting via ETS software (full range of functions)
- Setting via remote control/APP or APP (BLE)



### Technical data

LUXA 103 S360-28 KNX DE WH	
Installation height	2 - 4 m
Minimum height	1.7 m
Measuring range brightness	5 - 1000 lx
Detection angle	360°
Type of connection	KNX bus terminal
Installation type	Ceiling mounting
Light measurement	Mixed light measurement

LUXA 103 S360-28 KNX DE WH	
Switch-on delay presence	10 s - 30 min / inactive
Ambient temperature	-25°C ... 55°C
Detection range	140 m <sup>2</sup> (28 x 5 m   360°)
Colour	White
Type of protection	IP 54 (when fitted)
KNX Data Secure	✓

Subject to technical changes and misprints

additional information at: [www.theben.de/product/1039073](http://www.theben.de/product/1039073)

The load data are determined with exemplary selected illuminants and are therefore typical data due to the large number of available products.


# LUXA 103 S360-28 KNX DE WH

Item no.: 1039073


theben

Detection range for planning applications at a temperature of 21 °C

Mounting height (A)	Diagonally (T)	Head on to (R)	
2,5 m	140 m <sup>2</sup>   28 m x 5 m	70 m <sup>2</sup>   14 m x 5 m	
3 m	140 m <sup>2</sup>   28 m x 5 m	70 m <sup>2</sup>   14 m x 5 m	
3,5 m	104 m <sup>2</sup>   26 m x 4 m	60 m <sup>2</sup>   12 m x 5 m	



## Scale drawings



Subject to technical changes and misprints

additional information at: [www.theben.de/product/1039073](http://www.theben.de/product/1039073)

The load data are determined with exemplary selected illuminants and are therefore typical data due to the large number of available products.

15/06/2025

Page 2 of 3

# LUXA 103 S360-28 KNX DE WH

Item no.: 1039073



## Accessories

### theSenda P

Item no.: 9070910



### theSenda B

Item no.: 9070985




### theSenda S

Item no.: 9070911



### QuickSafe

Item no.: 9070531



Subject to technical changes and misprints

additional information at: [www.theben.de/product/1039073](http://www.theben.de/product/1039073)

The load data are determined with exemplary selected illuminants and are therefore typical data due to the large number of available products.