theRonda P360 Slave S WIN

Item no.: 2080053

Presence and motion detectors
Ceiling installation indoor

Description

- Passive infra-red presence detector for flush-mounted ceiling installation
- Circular detection area 360°, up to Ø 24 m (452 m²) at mounting height 3 m
- 1 channel light (Relay, 230 V)
- Automatic presence- and brightness-dependent control for lighting
- Mixed light measurement suitable for fluorescent lamps (FL/PL/ESL), halogen/incandescent lamps and LEDs
- Choice of fully or semi-automatic operation
- Adjustable brightness switching value, teach-in function
- Reduction of switch-off delay time in the event of short presence (brief-presence)
- Connection option for sensors or switches for manual switching with automatic recognition of sensor/switch
- Pulse function for staircase light time switch
- Switch-on delay and switch-off delay configurable
- Sensitivity adjustable
- Detection area can be limited using cover clip
- Ready for immediate use due to factory preset
- Test mode for checking function and detection area
- Extension of detection area via Master/Slave or Master/Master switching, a maximum of 10 detectors can be switched in parallel with each other
- Ceiling installation in flush-mounted socket
- Ceiling installation also possible with surface-mounted frame
- User remote control theSenda S, management remote control SendoPro (optional)

Technical data

	theRonda P360 Slave S WIN
Operating voltage	110 V AC - 230 V AC
Frequency	50 - 60 Hz
Maximum height	15 m
Minimum height	1.7 m
Installation type	Ceiling mounting, Indoor, Flush-mounted
Colour	White
Switching output	Slave
Power consumption	~

	theRonda P360 Slave S WIN
Light measurement	Mixed light measurement
Type of connection	Screw terminals
Detection range	452 m² (ø 24 m | 360°)
Detection angle	360°
Ambient temperature	50°C
Impact resistance	IK04
Type of protection	IP 54 (when fitted)

theRonda P360 Slave S WIN

Item no.: 2080053

Connection example



Detection range for planning applications at a temperature of 21 °C

Mounting height (A)	Sitting (S)	Diagonally (T)	Frontal gehend (R)
2 m	16 m² | 4.5 m	380 m² | 22 m	28 m² | 6 m
2.5 m	24 m² | 5.5 m	415 m² | 23 m	38 m² | 7 m
3 m	28 m² | 6 m	452 m² | 24 m	50 m² | 8 m
3.5 m	38 m² | 7 m	452 m² | 24 m	50 m² | 8 m
6 m		452 m² | 24 m	50 m² | 8 m
10 m		491 m² | 25 m	50 m² | 8 m





Detection range according to Sensnorm IEC 63180

Mounting height (A)	Diagonally (T)	Head on to (R)	Sitting (S)
2.5 m	434 m² | 23.5 m	55 m² | 8.4 m	50 m² | 8 m
10 m	707 m² | 30 m	79 m² | 10 m	
15 m	616 m² | 28 m	141 m² | 13.4 m	

theRonda P360 Slave S WIN

Item no.: 2080053

Scale drawings



Cut-out Ø 68 mm

Accessories

theSenda P
Item no.: 9070910

theSenda S
Item no.: 9070911

Masking clip
Item no.: 9070921

QuickSafe
Item no.: 9070531



theSenda B
Item no.: 9070985

Cover 110 GR
Item no.: 9070591

Cover 110 BK
Item no.: 9070851