

Wall mounted inlet

Part no. 361




- screw terminals
- for a suitable watertight protective cover see part no. 40434

Technical specifications

| | |
|-----------------------|-----------------|
| Ampere | 63 A |
| Poles | 5 p |
| Voltage | 400 V |
| Clock position | 6 h |
| Hertz | 50-60 Hz |
| Connection technology | Screw terminals |
| Contact | standard |
| Protection type | IP67 |
| Weight | 923 g |
| Certifications | VDE, CQC |

Drawing



| Drawing | Amp. | 63 | | | 125 | |
|--|------|-------|-------|-------|-----|-----|
| | | Poles | | | 4 | 5 |
| 2 MB 36 | | 3 | 4 | 5 | 4 | 5 |
| Dim. in mm | a | 170 | 170 | 170 | 264 | 264 |
| | b | 118 | 118 | 118 | 163 | 163 |
| | c | 171 | 171 | 171 | 205 | 205 |
| | d | 134.5 | 134.5 | 134.5 | 240 | 240 |
| | e | 103 | 103 | 103 | 140 | 140 |
| | f | 6,1 | 6,1 | 6,1 | 8,1 | 8,1 |
| | g | 6 | 6 | 6 | 8 | 8 |
| | h | 250 | 250 | 250 | 355 | 355 |
| | M | 40 | 40 | 40 | 50 | 50 |
| | M* | 2x40 | 2x40 | 2x40 | 50 | 50 |
| | a | 25° | 25° | 25° | 20° | 20° |
| Max. cable diam. (mm) | | 27 | 27 | 27 | 38 | 38 |
| Terminal for cond. cross section (mm²) min.-max. | | 6 | 6 | 6 | 16 | 16 |
| | | -16 | -16 | -16 | -35 | -35 |