

## Wall mounted receptacle DUO

Part no. 5113A



- screw terminals
- X-CONTACT
- switched
- mechanical DUO-interlock
- receptacles can be padlocked

## Technical specifications

|                       |                 |
|-----------------------|-----------------|
| Ampere                | 63 A            |
| Poles                 | 5 p             |
| Voltage               | 400 V           |
| Clock position        | 6 h             |
| Hertz                 | 50-60 Hz        |
| Connection technology | Screw terminals |
| Contact               | X-CONTACT       |
| Protection type       | IP67            |
| Enclosure material    | Plastic         |
| Weight                | 2564 g          |
| Certifications        | CQC             |

## Drawing

| Drawing<br>1 MB 180   | Amp.<br>Poles | 63     |        |        |
|---|---------------|--------|--------|--------|
|   |               | 3      | 4      | 5      |
| Dim. in mm  | a             | 260    | 260    | 260    |
|   | b             | 160    | 160    | 160    |
|   | c             | 198    | 198    | 198    |
|   | d             | 240    | 240    | 240    |
|   | e             | 140    | 140    | 140    |
|   | f             | 8.1    | 8.1    | 8.1    |
|   | g             | 8      | 8      | 8      |
|   | h             | 303    | 303    | 303    |
|   | M             | 40     | 40     | 40     |
|   | M*            | 2 x 40 | 2 x 40 | 2 x 40 |
| Max. cable diam. (mm)   |               | 27     | 27     | 27     |
| Terminal for cond. cross section (mm <sup>2</sup> ) min.-max. |               | 6      | 6      | 6      |
|   |               | -25    | -25    | -25    |