

Wall mounted receptacle DUO  
Part no. 5635A




- screw terminals
- switched
- mechanical DUO-interlock
- DIN rail
- receptacles can be padlocked

Technical specifications

|                       |                 |
|-----------------------|-----------------|
| Ampere                | 32 A            |
| Poles                 | 4 p             |
| Voltage               | 400 V           |
| Clock position        | 6 h             |
| Hertz                 | 50-60 Hz        |
| Connection technology | Screw terminals |
| Contact               | standard        |
| Protection type       | IP67            |
| Enclosure material    | Plastic         |
| Weight                | 2078 g          |
| Certifications        | CQC             |

Drawing



| Drawing                  | Amp.  | 16    |       |       | 32    |       | 63   |      |
|--------------------------|-------|-------|-------|-------|-------|-------|------|------|
|                          |       | 3     | 4     | 5     | 4     | 5     | 4    | 5    |
| 1 MB 181/620             | Poles |       |       |       |       |       |      |      |
| Dim. in mm               | a     | 364   | 364   | 364   | 364   | 364   | 460  | 460  |
|                          | b     | 134   | 134   | 134   | 134   | 134   | 180  | 180  |
|                          | c     | 160   | 162   | 163   | 168   | 168   | 202  | 202  |
|                          | d     | 347   | 347   | 347   | 347   | 347   | 440  | 440  |
|                          | e     | 117   | 117   | 117   | 117   | 117   | 160  | 160  |
|                          | f     | 6.3   | 6.3   | 6.3   | 6.3   | 6.3   | 8.1  | 8.1  |
|                          | g     | 8     | 8     | 8     | 8     | 8     | 8    | 8    |
|                          | h     | 391   | 395   | 398   | 408   | 411   | 505  | 505  |
|                          | M     | 32/40 | 32/40 | 32/40 | 32/40 | 32/40 | 40   | 40   |
|                          | M*    | 2x32  | 2x32  | 2x32  | 2x32  | 2x32  | 2x40 | 2x40 |
| Max. cable diam. (mm)    |       | 27    | 27    | 27    | 27    | 27    | 27   | 27   |
| Terminal for cond. cross |       | 1.5   | 1.5   | 1.5   | 2.5   | 2.5   | 6    | 6    |
| section (mm²) min.-max.  |       | —4    | —4    | —4    | —10   | —10   | —25  | —25  |