

**Panel mounted receptacle**  
Part no. 1127A




- screw terminals
- **X-CONTACT**
- straight
- receptacles with pilot contact: part no. + index P

**Technical specifications**

|                       |                 |
|-----------------------|-----------------|
| Ampere                | 63 A            |
| Poles                 | 5 p             |
| Voltage               | 230 V           |
| Clock position        | 9 h             |
| Hertz                 | 50-60 Hz        |
| Connection technology | Screw terminals |
| Contact               | X-CONTACT       |
| Protection type       | IP67            |
| Flange                | 107x100 mm      |
| Fixing hole           | 85x77 mm        |
| Weight                | 664 g           |
| Certifications        | VDE             |

**Drawing**



| Drawing<br>1 MB 212/258 | Amp.<br>Poles            | 63  |     |     | 125 |     |
|-------------------------|--------------------------|-----|-----|-----|-----|-----|
|                         |                          | 3   | 4   | 5   | 4   | 5   |
| Dim. in mm              | a                        | 107 | 107 | 107 | 130 | 130 |
|                         | b                        | 100 | 100 | 100 | 130 | 130 |
|                         | c                        | 81  | 81  | 81  | 119 | 119 |
|                         | d                        | 85  | 85  | 85  | 104 | 104 |
|                         | e                        | 77  | 77  | 77  | 104 | 104 |
|                         | f                        | 6   | 6   | 6   | 6.5 | 6.5 |
|                         | g                        | 12  | 12  | 12  | 18  | 18  |
|                         | g.1                      | 2   | 2   | 2   | 2   | 2   |
|                         | h                        | 117 | 117 | 117 | 129 | 129 |
|                         | i                        | 113 | 113 | 113 | 126 | 126 |
|                         | k                        | 55  | 55  | 55  | 43  | 43  |
|                         | l                        | 88  | 88  | 88  | 95  | 95  |
|                         | Terminal for cond. cross | 6   | 6   | 6   | 25  | 25  |
|                         | section (mm²) min.-max.  | —25 | —25 | —25 | —70 | —70 |