

## Wall mounted receptacle

Part no. 9372




- screw terminals
- highly resistant to chemicals
- with 2 external fixing points
- enclosure base can be turned 180°
- receptacles are designed for adding an auxiliary contact switch

## Technical specifications

|                       |  |
|-----------------------|--|
| Ampere                | 32 A   |
| Poles                 | 4 p  |
| Voltage               | 400 V  |
| Clock position        | 6 h  |
| Hertz                 | 50-60 Hz                                       |
| Connection technology | Screw terminals                                |
| Contact               | standard                                       |
| Protection type       | IP67   |
| Enclosure material    | Plastic, high resistance to chemicals / AMELAN |
| Weight                | 529 g  |
| Certifications        | VDE  |

## Drawing



| Drawing<br>1 MB 622                              | Amp.<br>Poles | 16                         |      |      | 32                         |      |      |
|--|---------------|----------------------------|------|------|----------------------------|------|------|
|  |               | 3                          | 4    | 5    | 3                          | 4    | 5    |
| Dim. in mm                                       |               |                            |      |      |                            |      |      |
| a  |               | 100                        | 100  | 100  | 100                        | 100  | 100  |
| b  |               | 101                        | 101  | 101  | 109                        | 109  | 109  |
| c  |               | 117                        | 125  | 131  | 157                        | 157  | 160  |
| d  |               | 50                         | 50   | 50   | 50                         | 50   | 50   |
| e  |               | 84                         | 84   | 84   | 92                         | 92   | 92   |
| f1   |               | 5.3                        | 5.3  | 5.3  | 5.3                        | 5.3  | 5.3  |
| f2   |               | 5.3                        | 5.3  | 5.3  | 5.3                        | 5.3  | 5.3  |
| g  |               | 6.5                        | 6.5  | 6.5  | 6.5                        | 6.5  | 6.5  |
| h  |               | 131                        | 131  | 132  | 148                        | 148  | 148  |
| i  |               | 24.7                       | 24.7 | 24.7 | 27.5                       | 27.5 | 27.5 |
| M  |               | 25 (optional M20)          |      |      | 32 (optional M25)          |      |      |
| M*   |               | 2x25 (blind) to be cut out |      |      | 2x25 (blind) to be cut out |      |      |
| Max. cable diam. (mm)                            |               | 18 (M25) and 15 (M20)      |      |      | 25 (M32) and 18 (M25)      |      |      |
| Terminal for cond. cross section (mm²) min.-max. |               | 1.5                        | 1.5  | 1.5  | 2.5                        | 2.5  | 2.5  |
|  |               | -4                         | -4   | -4   | -6                         | -6   | -6   |