

Connector SCHUKO

Part number: 10755



MENNEKES
Elektrotechnik GmbH & Co. KG

Aloys-Mennekes-Straße 1
57399 Kirchhundem
GERMANY

www.MENNEKES.org

Product Description

- screw connection technology
- protection against kinking
- strain relief
- for cables up to 3 x 2,5 mm², up to H07RN-F
- with lid

Technical Details

Connector SCHUKO	10755
Product serie	SCHUKO
Ampere	16A
Number of poles	2p+PE
Nominal voltage AC	230V
Protection type IP	IP44
Contact carrier	standard
X-CONTACT	no
Connection	screw terminals
Contact screw drive	PZ2, slot
Recommended wire end treatment for supply cable connection terminal	ferrule square gasproof crimped
Pilot contact	without pilot contact
Conductor cross-section max.	2.5 mm ²
Cable kink protection	with cable kink protection
Protective grommet	without protective grommet
Weight (net)	80 g
Packaging unit	10 pcs
EAN / identification number	4015394034872

Permissible ambient conditions

	Min.	Max.
Permanent ambient temperature	-5 °C	40 °C

Material properties

Housing	PA6 black [similar RAL 9005]
Lid	TPU natural colour [no RAL colour code]

Material resistance

The material resistance overview can be found on the website in the section “Knowledge” - “Product knowledge” - “Materials”.


Material and enviromental properties

RoHS 2011/65/EU incl. 2015/863/EU	✓
POP regulation (EU) 2019/1021	✓

Regulations and Standards

Norm	DIN VDE 0620-2-1
Declaration of Conformity	CE
Test label	VDE, EAC

Dimensional Drawing



Drawing
3 MB 39

Dim. in mm