

Specifications

Eaton 280350

Eaton xComfort ECO LV systems Final Distribution Boards. ECO Compact distribution board, surface mounted, 2-rows, 18 MU, IP40

General Specifications

PRODUCT NAME	Eaton xComfort ECO LV systems Final Distribution Boards
CATALOG NUMBER	280350
EAN	4015082803506
PRODUCT LENGTH/DEPTH	98 mm
PRODUCT HEIGHT	522 mm
PRODUCT WIDTH	410 mm
PRODUCT WEIGHT	2.66 kg
COMPLIANCES	RoHS conform
CERTIFICATIONS	EN 62208
MODEL CODE	BC-O-2/36-ECO



Powering Business Worldwide

Additional information

FITTED WITH: Device support rails
Neutral-protective
conductor terminal
Basic device

FUNCTIONS Basic device
Sealable

PROTECTION CLASS II (totally insulated)

RAL-NUMBER 9003

SPECIAL FEATURES

- IP40
- Protection Class II
- Plastic housing
white (RAL 9003)

USED WITH Installation distribution
board
ECO distribution board
Basic device

Delivery programme

APPLICATION Indoor (installation site)

COLOR White
Signal white (RAL 9003)

TYPE

- Basic device
- ECO distribution
board
- Installation
distribution board

Design verification to IEC/EN 61439

10.10 TEMPERATURE RISE	The panel builder is responsible for the temperature rise calculation. Eaton will provide heat dissipation data for the devices.
10.11 SHORT-CIRCUIT RATING	Is the panel builder's responsibility.
10.12 ELECTROMAGNETIC COMPATIBILITY	Is the panel builder's responsibility.
10.13 MECHANICAL FUNCTION	Meets the product standard's requirements.
10.2.2 CORROSION RESISTANCE	Meets the product standard's requirements.
10.2.3.1 VERIFICATION OF THERMAL STABILITY OF ENCLOSURES	Meets the product standard's requirements.
10.2.3.2 VERIFICATION OF RESISTANCE OF INSULATING MATERIALS TO NORMAL HEAT	Meets the product standard's requirements.
10.2.3.3 RESIST. OF INSUL. MAT. TO ABNORMAL HEAT/FIRE BY INTERNAL ELECT. EFFECTS	850 °C; meets the product standard's requirements.
10.2.4 RESISTANCE TO ULTRA-VIOLET (UV) RADIATION	Not relevant to indoor installations.
10.2.5 LIFTING	Does not apply to enclosures without lifting aids.
10.2.6 MECHANICAL IMPACT	IK05
10.2.7 INSCRIPTIONS	Meets the product standard's requirements.
10.3 DEGREE OF PROTECTION OF ASSEMBLIES	IP40
10.4 CLEARANCES AND CREEPAGE DISTANCES	Is the panel builder's responsibility.
10.5 PROTECTION AGAINST ELECTRIC SHOCK	Protection class 2, therefore not applicable.
10.6 INCORPORATION OF SWITCHING DEVICES AND COMPONENTS	Is the panel builder's responsibility.
10.7 INTERNAL ELECTRICAL CIRCUITS AND CONNECTIONS	Is the panel builder's responsibility.
10.8 CONNECTIONS FOR	Is the panel builder's

Design verification to IEC/EN 61439 - technical data

AMBIENT OPERATING TEMPERATURE DETAILS	-20 °C - 70 °C
--	----------------

EXTERNAL CONDUCTORS	responsibility.
10.9.2 POWER-FREQUENCY ELECTRIC STRENGTH	U _i = 400 V AC
10.9.3 IMPULSE WITHSTAND VOLTAGE	3.75 kV
10.9.4 TESTING OF ENCLOSURES MADE OF INSULATING MATERIAL	Meets the product standard's requirements.

Technical data - electrical

FREQUENCY RATING OF CONTACTS	50 Hz
-------------------------------------	-------

Technical data - mechanical

BUILT-IN DEPTH	70 mm
CABLE ENTRY POSTION	Metric cable entries on top and bottom
CLOSURE TYPE	Other
COVER/DOOR COLOR	Transparent
COVER/DOOR MODEL	Closed
COVER/DOOR TYPE	Door Single
DEGREE OF PROTECTION	IK05 (impact resistance) IP40
ENCLOSURE MATERIAL	Plastic
INTERNAL DEPTH	90 mm
MATERIAL	ABS (plastic)
MODULE RACK TYPE	Single-rail
MOUNTING METHOD	DIN-rail Surface mounting Surface mounted (plaster)
NUMBER OF MODULE SPACE UNITS PER ROW	18
NUMBER OF ROWS	2
PE AND N TERMINAL NUMBER AND CROSS SECTION	PE: 2 x (18 mm ² x 10 mm ²) N: 2 x (18 mm ² x 10 mm ²)
PROTECTIVE SHROUDING MATERIAL	Plastic
TERMINAL TYPE	Screw terminals
WIDTH IN NUMBER OF MODULAR SPACINGS	18

Temperature-rise verification as per IEC 60890

HEAT DISS. AMBIENT
35°C DELTA T:20°C WALL
MOUNT INDIVID. ENCL.
TOP (IEC 60890) 29 W

HEAT DISS. AMBIENT
35°C DELTA T:35°C WALL
MOUNT INDIVID. ENCL.
TOP (IEC 60890) 57 W

Resources

BROCHURES	eaton-xcomfort-compact-distribution-boxes-brochure-br014015en-en-us.pdf
CERTIFICATION REPORTS	eaton-xcomfort-eco-declaration-of-conformity-200416-en-us.pdf
DECLARATIONS OF CONFORMITY	eaton-lv-systems-declaration-of-conformity-eu25025en.pdf
DRAWINGS	eaton-lighting-xcomfort-eco-lv-systems-dimensions-006.eps
INSTALLATION INSTRUCTIONS	eaton-xcomfort-eco-installation-leaflet-il014002zu.pdf

PROJECT NAME:

PROJECT NUMBER:

PREPARED BY:

DATE:



Eaton Corporation plc Eaton House
30 Pembroke Road
Dublin 4, Ireland
Eaton.com

© 2026 Eaton. All Rights Reserved.

Follow us on social media to get the latest product and support information.

