

Specifications

Eaton 9PX1500RT

Eaton 9PX UPS, 2U, 1500 VA, 1350 W, 5-15P input, Outputs: (8) 5-15R, 120V



General specifications

PRODUCT NAME	Eaton 9PX UPS
CATALOG NUMBER	9PX1500RT
UPC	743172081261
PRODUCT LENGTH/DEPTH	17.7 in
PRODUCT HEIGHT	3.4 in
PRODUCT WIDTH	17.3 in
PRODUCT WEIGHT	42.5 lb
WARRANTY	3 year limited
COMPLIANCES	IEC 62040-2 Cat C1 CISPR22 Class B FCC part 15 Class B VCCI Class B
CERTIFICATIONS	cULus Listed NOM
GLOBAL CATALOG	9PX1500RT
PRODUCT TYPE	UPS

Battery

BATTERY MANAGEMENT	ABM technology (3-stage charging extends battery service life by 50% and provides advance warning for battery replacement)
BATTERY REPLACEMENT	Hot-swappable internal batteries and extended battery modules (EBMs). UPS battery replacement part # EBP-1613 (qty 1)
BATTERY TYPE	Valve Regulated Lead Acid (VRLA)
EXTENDED BATTERY CAPABILITY	Add up to 4 extended battery modules (EBM). Part number 9PXEBM48RT
RUNTIME AT FULL LOAD	5 min

Electrical input

INPUT CONNECTION	5-15P
INPUT CORD LENGTH	8 ft
INPUT NOMINAL VOLTAGE	100 VAC 110 VAC 120 VAC
INPUT FREQUENCY RANGE	60 Hz: 50–70 Hz, 50 Hz: 40–60 Hz
INPUT POWER FACTOR	>0.99 typical

Electrical output

RECEPTACLE	(8) 5-15R
TOPOLOGY	Online/Double-conversion
WATTAGE	1350 W
VA RATING	1500 VA
OUTPUT WAVEFORM	True sine wave
VOLTAGE	120V
OUTPUT POWER FACTOR	0.9
OUTPUT NOMINAL VOLTAGE	120V default (100/110/120/125V)
NOMINAL OUTPUT VOLTAGE	100V 110V 120V 125V
OUTPUT VOLTAGE RANGE	±1% steady-state
OUTPUT FREQUENCY	50/60 Hz

Communications

COMMUNICATION	MiniSlot + 1 USB port + 1 serial RS232 port + 1 mini-terminal block for remote ON/OFF + 1 mini-terminal block for remote power off + 1 mini-terminal block for output relayCommunication slot
EXPANSION SLOTS	• (1) Mini-Slot (MS) expansion port. The following optional connectivity cards may be ordered separately. • Gigabit Network Card part number: NETWORK-M3 • Modbus card part number: INDGW-M2 • Relay card part number: RELAY-MS
SOFTWARE COMPATIBILITY	Intelligent Power Software Suite
USER INTERFACE	Graphical display, 5-button programmable menu

Environmental	
ALTITUDE	0-1500m (0° to 40°C), 1500-3000m (0° to 35°C)
BTU RATING	Online: 512, Battery: 897
NOISE LEVEL	<40 dB at 1 meter
RELATIVE HUMIDITY	0-96% non-condensing
TEMPERATURE RANGE	0° to 40°C (32° to 104°F)

Additional specifications	
RACK SIZE	2U
RACK MOUNTING KIT	Yes
EFFICIENCY AT MAX. LOAD	90
PACKAGE CONTENTS	• 1500VA 1350W 120V 9PX Online Double-Conversion UPS with 8 Outlets • USB cable • RS-232 cable • Rack-mounting hardware • Tower support stands • Safety guide • Quick Start Guide
INTERNAL BYPASS	Yes

Warranty and support

STANDARD FACTORY WARRANTY

- 3-YEAR FACTORY WARRANTY
- - 3 years
- - Parts, electronics and batteries coverage
- - Standard ground shipping
- - Technical support

EXTENDED SERVICE PLANS

- ADVANCED DEPOT EXCHANGE
- - 5-year depot repair: 9SW5Y-1500UC
- - Expedited parts coverage for 5 years
- - Parts, electronics and UPS batteries coverage
- - Next business day shipping
- - Technical support
- 5-YEAR ON-SITE PLAN: WFLN75XX-2509UC
- - On-site parts and labor coverage for years 5
- - Parts, electronics and UPS batteries coverage
- - 24x7 on-site labor coverage, next-day response
- - Next-day shipping
- - Technical support

Resources

BROCHURES

[Eaton UPS Services Quick Guide - EN](#)

[Eaton 9PX 700-3000 VA UPS brochure](#)

[Eaton UPS and battery services - EN](#)

DRAWINGS

[Eaton 9PX UPS 700-1500 VA 120V outline drawing](#)

[Eaton 9PX UPS 700-1500 VA technical drawing](#)

[Battery Integration System Pro-E drawing](#)

[9PX 2-post rack kit user guide](#)

MANUALS AND USER GUIDES

[9PX battery integration system user guide](#)

[9PX 700-3000 VA 2U UPS user guide](#)

SPECIFICATIONS AND DATASHEETS

[Eaton 9PX UPS guide specification: 700-3000 VA](#)

[9PX 700-3000 VA UPS technical specification](#)

[Eaton Specification Sheet - 9PX1500RT](#)

WARRANTY GUIDES

[9PX three year limited warranty](#)

PROJECT NAME:
PROJECT NUMBER:
PREPARED BY:
DATE:



Eaton Corporation plc Eaton House
30 Pembroke Road
Dublin 4, Ireland
Eaton.com

© 2026 Eaton. All Rights Reserved.

Follow us on social media to get the latest product and support information.

