

PK 1-100 M10-M10 1p 1000V

Fuse - base



ETI Code:	004123400
IP rating:	IP00
Type description:	PK
Size:	NH1/85
Number of poles:	1
Rated current:	250 A
Rated AC voltage:	1000 V
Rated DC voltage:	1000 V
Breaking capacity AC:	200 kA
Type of installation:	Base plate mounting
Overvoltage category:	III
Standards:	IEC 60269-2
Ambient temperature:	-25/55 °C
Conventional free air thermal current with fuse links:	250 A
Conventional free air thermal current with solid links:	320 A
Max. permissible power dissipation per fuse link:	32 W
Rated operating mode:	Uninterrupted
Pollution degree:	3
Rated frequency:	40/60 Hz

Online product page [🔗](#)

Documents



TECHNICAL DATA CATALOG



INSTRUCTION MANUAL



2D FILE



3D FILE



EPLAN FILE

ETIM

Mounting method

Screw-on

Construction size

Other

Number of poles

1

Connection type

Screwed terminal

Rated current

250 A

Logistics

Product

EAN code for a single product	3838400061713
Net weight of the product	0.623 kg
Net width	55 mm
Net height	216 mm
Net depth	83.6 mm
Stock unit of measure	pcs

Basic Packaging

Basic packaging quantity	3 pcs
EAN code for a basic packaging	3838895765011
Basic packaging weight	2.009 kg
Basic Packaging Dimensions Height	0.119 m
Basic Packaging Dimensions Width	0.165 m
Basic Packaging Dimensions Depth	0.24 m
Basic packaging volume	0.005 m³

Transport Packaging

Transport packaging quantity	15 pcs
EAN code for a transport packaging	3838895765028
Transport packaging weight	10.5 kg
Transport Packaging Dimensions Height	0.285 m
Transport Packaging Dimensions Width	0.343 m
Transport Packaging Dimensions Depth	0.363 m
Transport packaging volume	0.035 m³
Pallet quantity	270 pcs
Customs tariff	85389099