

# Specifikācijas



Foto ir ilustratīvs



## Eaton PB1D

Eaton Protection Box 1 DIN, 10A, Input: Schuko, Output: (1) Schuko

### Vispārējā informācija

|                      |                                   |
|----------------------|-----------------------------------|
| PRODUCT NAME         | Eaton Protection Box              |
| CATALOG NUMBER       | PB1D                              |
| EAN                  | 3553340667152                     |
| PRODUCT LENGTH/DEPTH | 98 mm                             |
| PRODUCT HEIGHT       | 55 mm                             |
| PRODUCT WIDTH        | 72.5 mm                           |
| PRODUCT WEIGHT       | 0.115 kg                          |
| COMPLIANCES          | CE Marked<br>EAC                  |
| CERTIFICATIONS       | IEC/EN 60884-1<br>IEC/EN 61643-11 |
| MODEL CODE           | Eaton Protection Box 1<br>DIN     |

## Vairāk papildu specifikācijas

|                  |                                                                                                                                   |
|------------------|-----------------------------------------------------------------------------------------------------------------------------------|
| AMPERAGE RATING  | 10A                                                                                                                               |
| INDICATOR TYPE   | Color LED                                                                                                                         |
| MATERIAL         | Plastic                                                                                                                           |
| SPECIAL FEATURES | High end surge protection device implementing Schuko (DIN) socket, IEC 61643-11 compliant, including connected equipment warranty |
| TYPE             | Surge Suppressor                                                                                                                  |

## Izejas pārsprieguma impulsu ierobežotāja specifikācijas

|                                                  |                                                                                                      |
|--------------------------------------------------|------------------------------------------------------------------------------------------------------|
| ANGLE OF ROTATED CENTRAL INSERT                  | Other                                                                                                |
| CIRCUIT BREAKER                                  | No                                                                                                   |
| COLOR                                            | Black/white                                                                                          |
| CORE CROSS SECTION                               | 0 mm <sup>2</sup>                                                                                    |
| DEGREE OF PROTECTION                             | IP20                                                                                                 |
| HALOGEN FREE                                     | No                                                                                                   |
| HOUSING SHAPE                                    | Rectangular                                                                                          |
| INPUT CONNECTION                                 | Protective contact (SCHUKO)                                                                          |
| INTERNET/TEL LINE PROTECTION                     | No                                                                                                   |
| MATERIAL                                         | Plastic                                                                                              |
| MATERIAL QUALITY                                 | Other                                                                                                |
| NEMA DESIGNATION                                 | None                                                                                                 |
| NOMINAL FREQUENCY                                | 50-60 Hz                                                                                             |
| NUMBER OF COLD DEVICE SOCKET OUTLETS             | 8                                                                                                    |
| NUMBER OF NEMA-OUTLETS                           | 0                                                                                                    |
| NUMBER OF OUTLETS                                | 1                                                                                                    |
| NUMBER OF OUTPUTS (OTHER)                        | 8                                                                                                    |
| NUMBER OF SOCKET OUTLETS WITH PROTECTIVE CONTACT | 1                                                                                                    |
| NUMBER OF USB CONNECTIONS                        | 0                                                                                                    |
| OPERATING TEMPERATURE - MAX                      | 40 °C                                                                                                |
| OPERATING TEMPERATURE - MIN                      | 0 °C                                                                                                 |
| OPERATING VOLTAGE                                | 220-250 V                                                                                            |
| PACKAGE CONTENTS                                 | <ul style="list-style-type: none"><li>• Surge suppressor device</li><li>• Quickstart guide</li></ul> |
| POWER CORD LENGTH                                | 0                                                                                                    |
| RAL-NUMBER                                       | 9003                                                                                                 |
| RESIDUAL CURRENT CIRCUIT BREAKER                 | No                                                                                                   |
| FITTED WITH:                                     | Fuse<br>Over voltage protection<br>LED indication                                                    |
| SURFACE FINISH                                   | Matt/Matte                                                                                           |

## Pārsprieguma aizsardzības ierīces specifikācijas

|                        |                |
|------------------------|----------------|
| <b>MOUNTING METHOD</b> | 35 mm DIN rail |
| <b>PHASE</b>           | Single-phase   |
| <b>SURGE CURRENT</b>   | 3000A          |

|                           |        |
|---------------------------|--------|
| <b>SURFACE PROTECTION</b> | Other  |
| <b>SURGE RATING</b>       | 1500 V |
| <b>SWITCHABLE</b>         | Yes    |
| <b>TRANSPARENT</b>        | No     |

## Informatīvie materiāli

**PROJEKTA NOSAUKUMS:**

**PROJEKTA NUMURS:**

**SAGATAVOJA:**

**DATUMS:**



**Eaton Corporation plc** Eaton House  
30 Pembroke Road  
Dublin 4, Īrija  
Eaton.com

© 2026 Eaton. Visas tiesības paturētas

Seko jiet mums sociālajos medijos, lai  
saņemtu produktu jaunumus un  
atbalsta informāciju.

