ED2S 160/3

Blokslēdzis

ETI kods:	**004671281**
Pieteikums:	**IEC 60947-3**
Nominālā strāva:	**160 A**
Polu skaits:	**3**
Savienojuma tips:	**Priekinė jungtis**
Standarti:	**IEC 60947-3**
Nominālais impulsa izturības spriegums Uimp (kV):	**8 kV**
Izmantošanas kategorija:	**AC-23A, DC-22A**
Nominālā īssavienojumu veidošanas jauda Icm:	**2,8 kA**
Nominālā īstermiņa noturības strāva Icw pie 0,3 s:	**2 kA**
Nominālais darba spriegums (V AC):	**690 V**
Nominālais darba spriegums (V DC):	**250 V**
Nominālais izolācijas spriegums (V):	**690 V**
Funkcija:	**Switch Disconnector**
Korpusa izmērs:	**160**
Īsslēguma jauda:	**2.8 kA**

Produkta tiešsaistes lapa

Dokumenti

TEHNISKO DATU KATALOGS

DEKLARĀCIJA

2D FAILS

ETIM

Version as maintenance-/service switch	✓
Suitable for floor mounting	✓
Rated permanent current Iu	**160 A**
Type of control element	**Rocker lever**
Conditioned rated short-circuit current Iq	**2,8 kA**
Type of electrical connection of main circuit	**Screw connection**
Degree of protection (IP), front side	**IP20**
Voltage release optional	✓
Number of poles	**3**
Device construction	**Built-in device fixed built-in technique**
Version as main switch	✓

Loģistika

Produkts

Svars	**0,7 kg**
Stock unit of measure	**pcs**

Transporta iepakojums

Transport packaging quantity	**1 pcs**
EAN code for a transport packaging	**3838895665625**
Transport packaging weight	**1,6 kg**
Transport Packaging Dimensions Height	**110 mm**
Transport Packaging Dimensions Width	**170 mm**
Transport Packaging Dimensions Depth	**110 mm**
Transport packaging volume	**2,057 dm³**
Pallet quantity	**300 pcs**
Customs tariff	**85362090**