GF3 SLIM RG4.5 - Guiding head with front thread

for fiberglass rod Ø 3 mm, thread RTG Ø 3 mm
Item no.: **20956**

VIDEO
GF3 SLIM
Click here Video


KG 100

PATENTED

Click here Productinformation



Only Ø 4,5 mm




Stowable in the GF3 SLIM accessory box



*Musterbild - Box nicht enthalten


Application -
FTTH fiberglass installation



Speedpipe from Ø 5 mm Innerdiameter

Ideally suited for occupied pipes

RG4.5 - Guiding head Ø 4,5 mm



DATA

ITEM NO.:	**20956**
WEIGHT	0,0037 kg
DIMENSION GUIDING HEAD + EYELET	L 68 x W 13,50 x H 4,50 mm
BREAKING LOAD	100 kg
MATERIAL	Stainless steel
EAN-CODE	9120045477740

ADVANTAGES

- Patented RG4.5 - Guiding head RTG Ø 3 mm
- Incl. swivel
- Ideal for retrofitting occupied pipes or laying glass fibre cables
- Breaking load 100 kg
- Stainless steel

DESCRIPTION

The patented RG4.5 - Guiding head with front thread (RTG Ø 3 mm) including swivel is ideal for the GF3 SLIM fiberglass rod Ø 3 mm. With a maximum diameter of only Ø 4.5 mm, the guiding head is well-suited for retrofitting occupied pipes or laying fiber optic cables (FTTH - Fiber to the Home). Breaking load: 100 kg

Application film: you can watch a short, very informative application film by scanning the QR code or on www.runpotec.com.

Scope of supply: 1 x RG4.5 Guiding head with front thread RTG Ø 3 mm including swivel, 1 x pulling eyelet Ø 4.5 mm, 1 x starting head Ø 4.5 mm

INFORMATION

Use with:

GF3 SLIM - Cable pulling tool incl. digital meter counter
20 m - Item no.: 10207
30 m - Item no.: 10208
50 m - Item no.: 10209



Click here Productinformation

GF3 SLIM - Cable pulling tool without meter counter
20 m - Item no.: 10210
30 m - Item no.: 10211
50 m - Item no.: 10212



Click here Productinformation

GF3 SLIM Replacement fiberglass Ø 3 mm
20 m - Item no.: 20952
30 m - Item no.: 20953
50 m - Item no.: 20954



Click here Productinformation